

**1. PROPRIETARY PRODUCT/MANUFACTURER**

1.1. **Proprietary Product:** Performa heterogeneous commercial flooring designed for heavy commercial interiors. With contemporary visuals, stylish designs of wood and stone, 25 mil wear layer, and a nitrogen cured polyurethane coating.

**1.1. Recommended areas for use:**

- Healthcare – Patient rooms, exam rooms, lobbies, corridors, emergency rooms, critical care, laboratories
- Education – Classrooms, corridors, multipurpose rooms, gymnasiums, laboratories, cafeterias
- Offices – Break rooms, offices, corridors, cafeterias, lavatories
- Retail – Sales areas, offices
- Hospitality – Corridors, vending areas, lobbies, bathrooms

**1.2. Manufacturer:**

Tarkett North America      Phone: (800) 899-8916  
30000 Aurora Rd.                      (440) 543-8916  
Solon, Ohio 44139  
Web: [www.tarkettna.com](http://www.tarkettna.com)

**1.3. Proprietary Product Description:**

1.3.1. **Construction:** Performa has a PUR reinforced wearlayer composed of 90% binder content, with a polyurethane reinforced (PUR) construction to minimize maintenance.

**1.3.2. Styles:**

- Overall thickness: 0.080" (2.0 mm)
- Wear layer thickness: 25 mil (0.64 mm)
- Surface treatment: Nitrogen cured PU
- Pattern: Wood & Stone
- Packaging: Available in 6 ft. (1.83 m) and 12ft. (3.67 m) wide

**2. PRODUCT PERFORMANCE AND TECHNICAL DATA**

- 2.1. **Sheet material** meets ASTM F 1303, Type I, Grade 1, Class B performance sheet vinyl floorcovering with backing
- 2.2. **Heat Stability by Color Change** (ASTM F 1514):  $\Delta E \leq 8$
- 2.3. **Light Stability by Color Change** (ASTM F 1515):  $\Delta E \leq 8$
- 2.4. **Flexibility** (ASTM F 137): Passes
- 2.5. **Chemical Resistance** (ASTM F925): Passes
- 2.6. **Static coefficient of friction** (ASTM D 2047):  $\geq 0.5$
- 2.7. **Static Load Limit** (ASTM F 970): 175 PSI ( $< 0.005$ " residual indentation)
- 2.8. **Acoustical** (ASTM E2179):  $\Delta IIC 8$
- 2.9. **Flammability** (Flooring Radiant Panel): ASTM E 648, Class 1
- 2.10. **Smoke Development** (ASTM E662):  $< 450$

**3. INSTALLATION**

3.1 See heterogeneous sheet flooring installation instructions for complete details.

**3.2. Roll Adhesive:**

- **Tarkett 925 Adhesive Coverage:**  
Porous Substrate: 250-300 sq. ft./gal.  
Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**  
Porous & Non-porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett RollSmart Adhesive Coverage:**  
Approximate Coverage:  
Porous & Non-porous Substrate: 350 - 400 sq. ft. per gallon (3/8" Nap Paint Roller used with a paint tray)
- **Tarkett Cold Weld Liquid Coverage:**  
175 – 200 lin. ft. per. 4.5 oz. tube

**4. AVAILABILITY AND COST**

Available through authorized Tarkett distributors nationwide.

**5. MAINTENANCE**

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Acczent Maintenance Instructions for complete maintenance details.

**6. TECHNICAL SERVICES**

Visit us on the web at [www.tarkettna.com](http://www.tarkettna.com)

Contact Technical Support at (800) 899-8916 or E mail: [Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

**7. LIMITED WARRANTY**

Limited 10 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

**Tarkett North America**

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkettna.com](http://www.tarkettna.com)