

Terra-Turf®

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product**: Terra-Turf Entrance Matting

1.2. Manufacturer:

Tarkett North America 30000 Aurora Rd. Solon, Ohio 44139 Web: www.tarkettna.com Phone: (800) 899-8916

1.3. Proprietary Product Description:

1.1.1. Construction: Tarkett Terra-Turf Rubber Floor Tiles are manufactured of recycled aircraft and truck tire strips adhered with hot-melt adhesive to a reinforced nylon scrim backing. This rugged, yet handsome, carpet-like tile is highly resistant and spike-proof. Its non-skid surface is ideal for ramps, concourses, golf pro shops, entrances, skating rinks, schools, and other sports arenas. Tarkett Terra-Turf Rubber Floor Tiles are designed for interior or exterior applications, but not recommended for commercial kitchen environments.

1.3.1. Physical Characteristics:

• Color: Black/brown

Size/Packaging:

12" x 12" x 3/8" thickness (30.48 cm x 30.48 cm - 9.53 mm thickness)

12" x 25 ft. coils x 3/8" thickness (30.48 cm x 7.62 m - 9.53 mm thickness)

25 tiles or 1 coil per carton.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Hardness (ASTM D 2240): Not less than 85 Shore A
- 2.2. Abrasion Resistance (ASTM D 3389): <1.0 gm weight loss
- Slip Resistance (ASTM D 2047): Exceeds static coefficient of friction of 0.5
- 2.4. Fire Resistance (ASTM D2859): Passes

3. INSTALLATION

See Terra-Turf installation instructions for complete details.

3.1. Adhesives:

Tarkett Terra-Turf Adhesive Coverage:

Porous Substrate: 125-150 sq. ft. per gallon Non-porous Substrate: 150-175 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

WARRANTY

Limited 5 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Terra-Turf maintenance instructions for complete details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.