

Product Description

Stamping Release is designed to create a lubricant and release membrane between imprinting tools and the concrete surface. It creates non-uniform coloration, thereby creating a marble effect on fresh concrete surfaces.

Primary Application(s)

- Prevents stamping tools from sticking to the surface of freshly poured concrete
- Adds non-uniform color to the surface of the concrete, creating a marble effect

Benefits

- Non-bleeding
- Color fast
- Resistant to alkali
- Water insoluble
- Creates a non-stick membrane between the imprint tool and the concrete surface, allowing release of the tool with minimal cleaning

Packaging

Stamping Release is sold in 13.6 kg (30 lb) boxes.

Storage

Store in a cool, dry area. Protect from moisture. Keep away from acids.

Properties

- **Appearance:** Dry powder (assorted colors)
- **Bulk Density:** Not available
- **Odor:** None
- **pH:** Not applicable

Coverage/Dosage


89–93 m² per 13.6 kg box (900–1000 ft² / 30 lb)

Directions

Because settling may occur during shipping, mix product prior to use.

Spreading: After the bleed water has disappeared, spread Stamping Release across the surface with a brush or from a burlap bag. The stamping process should immediately follow the application of the release powder.

Finishing: Allow the concrete to cure for 24 to 36 hours. After the curing time has elapsed, use a soft broom to sweep away as much excess release powder as desired. Do not apply excessive pressure or the concrete surface



may be damaged. Wash with Interstar's KOPA Stamping Release Cleaner and water. We recommend Interseal 22G, Interstar's acrylic sealer, to protect the surface and enhance its color.

Curing: It is not necessary to use a curing agent or other method of curing with Interstar Stamping Release.

Safety

Avoid all contact with skin and eyes. Wear protective equipment when handling. For additional information, please refer to the Product Safety Data Sheet (SDS).

Availability

Interstar products are available throughout Canada, the United States and Mexico. Please contact our Customer Service Department (1-800-567-1857) to place an order or to find a distributor in your area.

Technical Services

Interstar's technical staff and chemists are always available to offer their expert advice. Should you need technical assistance, please call 1-800-567-1857.

Warranty

The limit of liability of this company shall be the purchase price paid by the user or buyer for the quantity of the Interstar product involved. See Interstar's Warranty for complete details.