

Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page 1 of 6

SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Identifier : S-309 Once 'N Done Floor Cleaner Ready-To-Use

Product Code : 70047933 Trade Name/Synonyms : S-309

Recommended Use : Floor Cleaner, Ready-To-Use. Uses Advised Against : No information available.

Supplier's name and address:

Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA, USA 17603

Information Telephone No. : (800) 233-3823

Website Address : http://www.floorexpert.com

24 Hr Emergency Telephone # : CHEM-TEL: 1-800-255-3924 OR 1-813-248-0585 (call collect)

SECTION 2 – HAZARDS IDENTIFICATION

GHS Classification per 29 CFR 1910.1200 (OSHA HCS 2012) and HPR (WHMIS 2015)

Not classified as hazardous.

GHS Pictograms

None.

Signal Word

None.

Hazard Statements

None.

Safe Handling Instructions: Avoid eye and skin contact. It is recommended to use safety glasses and

gloves during handling. During installation process, adequate ventilation of the work area should be maintained. Although the product is low in VOCs, persons who are sensitive to odors or chemicals should avoid the work area during

installation. Keep container closed.

Hazards Not Otherwise Classified

None.

% With Unknown Acute Toxicity : Less than 1% by weight of this product consists of ingredients with unknown

acute toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS#	% (by weight)
2-Butoxyethanol	111-76-2	0.1 – 1.0

SECTION 4 – FIRST AID MEASURES

General : Call a doctor if you feel unwell.

Inhalation : If inhaled, remove person to fresh air and keep at rest in a position comfortable for

breathing. If breathing problems persist, seek medical attention/advice.

Skin contact : Remove contaminated clothing immediately. Wash skin with plenty of water. If

irritations or symptoms develop, seek medical attention/advice.

Eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing for 15 minutes. Get medical advice/attention.

Ingestion : Rinse mouth. Do NOT induce vomiting. Call a doctor/physician if you feel unwell.



Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823

Page 2 of 6

Notes for Physician : Treat symptomatically.

Signs and symptoms of short-term (acute) exposure

Inhalation : None known.

Skin : Symptoms may include mild redness or itching.

Eyes : Symptoms may include mild redness, itching, or pain.

Ingestion : None known.

Effects of long-term (chronic) exposure

: None known.

Indication of need for immediate medical attention or special treatment

: Difficulty breathing persists after removing the person to fresh air.

Any exposure to the eye which causes irritation.

SECTION 5 – FIRE FIGHTING MEASURES

Suitable extinguishing media

: Carbon dioxide, dry chemical powder, alcohol resistant foam or water spray.

Unsuitable extinguishing media

: Water jet may spread the burning material.

Hazardous combustion products

: Carbon dioxide; Carbon monoxide; Ammonia; Nitrogen oxides as well as other toxic

vapors and gases which are common to thermal degradation of organic

compounds.

Special fire-fighting procedures/equipment

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. After fires have been extinguished, carefully clean all

equipment and surfaces exposed to fumes.

Environmental precautions

Do not allow large amounts of this product to enter drains or contaminate ground

water system.

Fire hazards/conditions of flammability

: Not flammable under normal conditions of use. Closed containers may rupture if

exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.1200, WHMIS 2015)

: Not flammable.

NFPA Rating : <u>0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe</u>

Health: 1 Flammability 1 Instability 0 Special Hazards: None

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions : Restrict access to area until completion of clean-up. All persons dealing with

clean-up should wear the appropriate chemically protective equipment.

Protective equipment : Refer to Section 8 for additional information on acceptable personal protective

equipment.

Emergency Procedures: This product does not contain chemicals requiring EPA notification for spills.

Methods and materials for containment and cleaning up

: Ventilate area of release. Stop spill or leak at source if safely possible. Caution: floor surfaces will be slippery! Contain product with inert absorbent material, preventing it from entering sewer lines or waterways. Gather up spilled material and place in suitable container for later disposal (see Section 13). Residual of product, while still wet, can be cleaned up with water. Notify the appropriate authorities as required.

Prohibited materials : None known.

Environmental precautions : Do not allow large amounts of this product to enter drains or waterways, or

contaminate ground water systems. Small amounts, such as used to clean floors,

etc. may be disposed of by pouring down a drain.



Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603

Telephone: (800) 233-3823 Page 3 of 6

Reference to other sections : See Section 14 for disposal information.

SECTION 7 – HANDLING AND STORAGE

Safe handling procedures : Wear suitable protective equipment during handling. (See Section 8.) Observe

good hygiene standards. Use only with adequate ventilation. Wash thoroughly after

handling. Avoid contact with eyes, skin, or clothing.

Store in a cool, dry, well-ventilated area. Store away from heat and open flame. Storage requirements

Store in original container. Keep tightly closed when not in use.

Incompatible materials See Section 10.

Special packaging materials No special requirements.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

: No exposure limits have been established for the product itself. Below are exposure **Permissible Exposure Limits**

limits for the components in the product.

Ingredients	CAS#	ACGII	H TLV	OSHA PEL		
		TWA STEL		PEL STEL		
				50 ppm		
2-Butoxyethanol	111-76-2	20 ppm	N/Av	(skin)	N/Av	

: Use general or local exhaust ventilation to maintain air concentrations below **Engineering Controls**

recommended exposure limits. Ventilation should effectively remove and prevent

buildup of any vapor generated from the handling of this product.

Personal Protection Equipment

Note : The following PPE recommendations are for professional users. Consumer users should

refer to the product label.

Eye / face protection : Eye protection such as chemical goggles or safety glasses is recommended.

Skin protection Wear gloves which are impervious to the product. Glove materials such as rubber

or vinvl are recommended.

Body protection Where extensive exposure to product is possible, use resistant coveralls, apron and

boots to prevent contact.

Respiratory protection Under normal working conditions, respiratory protection is not necessary when

> using this product as recommended. If work process generates excessive quantities of vapor, or exposures in excess of any PEL, wear an appropriate

organic vapor respirator.

Site safety equipment An eyewash station and safety shower should be made available in the immediate

working area.

Avoid contact with eyes, skin and clothing. Upon completion of work, wash hands General hygiene considerations

thoroughly. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquid **Appearance** Greenish-yellow

Odor **Odor threshold** : Ammonia : N/Av pН 9.5 - 10.5Specific gravity : 1.00 212°F (100°C) Coefficient of water/oil distribution **Boiling point** : N/Av Melting/Freezing point Solubility in water N/Av : Miscible Vapor pressure (mm Hg @ 20°C / 68°F) : N/Av Evaporation rate (n-Butyl acetate = 1) : N/Av Vapor density (Air = 1) : N/Av Volatiles (% by weight) : > 95 %

Volatile organic compounds (VOCs) : 0.47% per CARB rules

Particle size : N/Av Flammability classification : Not flammable



Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page 4 of 6

Flash point : >93.3°C (>200°F) Lower flammable limit (% by vol) : Not available
Flash point method : Setaflash closed Upper flammable limit (% by vol) : Not available
Auto-ignition temperature : N/Av Decomposition temperature : Not available
Viscosity : N/Av Oxidizing properties : Not available

Explosion data: Sensitivity to mechanical impact / static discharge

: Not expected to be sensitive to mechanical impact or static discharge.

SECTION 10 – REACTIVITY AND STABILITY INFORMATION

Reactivity : Not reactive.

Stability : Stable under the recommended storage and handling conditions prescribed.

Hazardous reactions : Hazardous polymerization does not occur.

Conditions to avoid : Extreme heat.

Materials to avoid and incompatibility

: Strong oxidizing agents.

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of exposure : Inhalation: YES Skin Absorption: NO Skin and Eyes: YES Ingestion: YES

Toxicological data : See below for individual ingredient acute toxicity data.

	LC50 (4 hr)	LD50			
Ingredients	Inhalation, rat	Oral, rat	Dermal, rabbit		
2-Butoxyethanol	2.17	917	220		

Skin corrosion or irritation : May cause mild irritation to skin.

Serious eye damage / eye irritation : May cause mild, temporary irritation to eyes.

Respiratory or skin sensitization : None known.

Germ cell mutagenicity : None known.

Carcinogenic status : Does not contain any chemical listed as a carcinogen by IARC, NTP, or OSHA in

concentrations greater than 0.1%. ACGIH classifies 2-butoxyethanol in group A3—

a confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity : None known.

Specific Target Organ Toxicity, Single Exposure

: None known.

Specific Target Organ Toxicity, Repeated Exposure

: None known.

Aspiration hazard : None known.
Additional information : N/Av

SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : Under normal conditions of use, this product may be disposed of by pouring down a

drain.



Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page **5** of **6**

Ecotoxicity : No data available.
Biodegradability : No data available.
Bioaccumulative potential : No data available.
Mobility in soil : No data available.
PBT and vPvB assessment : No data available.
Other adverse effects : No data available.

SECTION 13 – DISPOSAL CONSIDERATION

Handling for disposal : Handle waste according to recommendations in Section 7.

Methods of disposal : Dispose in accordance with all applicable federal, state, provincial and local

regulations. Contact your local, state, provincial or federal environmental agency

for specific rules.

Packaging : Handle contaminated packaging in the same manner as the product.

RCRA : For disposal of unused or waste material, check with local, state and federal

environmental agencies.

SECTION 14 – TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	This product is not regulated according to Canadian TDG regulations.	None	None	None
TDG Additional Information	None			•	
49 CFR/DOT	None	This product is not regulated according to US DOT regulations.	None	None	None
49 CFR/DOT Additional Information	None			•	

IATA : Not regulated for Air Transport

IMDG : Not regulated for Ocean Transport

SECTION 15 – REGULATORY INFORMATION

Canadian Information:

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR). This SDS contains all of the information required by the HPR.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on either the Domestic Substances List (DSL) or the Non- Domestic Substances List (NDSL).

US Federal Information:

TSCA: All ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): None reported.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Not Hazardous.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product is not subject to SARA notification requirements, since it does not contain any Toxic Chemical constituents above *de minimus* concentrations.

U.S. State Right To Know Laws

California Proposition 65: None



Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA USA 17603 Telephone: (800) 233-3823 Page 6 of 6

Other State Right to Know Laws:

Ingredient on State RTK Law?	CAS No.	CA	MA	MN	NJ	NY	PA	RI
2-Butoxyethanol	111-76-2	Yes	Yes	Yes	Yes	No	Yes	Yes

SECTION 16 – OTHER INFORMATION

HMIS Rating : *- Chronic Hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 1 Flammability 1 Physical Hazard: 0 PPE: Gloves, safety glasses

Legend : ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability

Act of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substances List EPA: Environmental Protection Agency GHS: Globally Harmonized System HPR: Hazardous Products Regulations

IARC: International Agency for Research on Cancer

Inh: Inhalation N/Av: Not Available N/Ap: Not Applicable

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TSCA: Toxic Substance Control Act TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

Disclaimer of Liability

The Information presented herein is supplied as a guide to those who handle or use this product and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive. The manner and conditions of use and handling may involve other and additional considerations. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

No warranty of any kind is given or implied. Armstrong Flooring, Inc. will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information contained herein.

Prepared By:

Armstrong Flooring, Inc. 2500 Columbia Ave. Lancaster, PA, USA 17603

(800) 233-3823

Visit our Website: http://www.floorexpert.com

Revision date: : 01-Jul-2019

End of Document