

Mapecontact LT

Moisture-Resistant Tape for Landscape Synthetic Turf Installation



DESCRIPTION

*Mapecontact*TM *LT* is a single-sided, moisture-resistant tape for the rapid installation of synthetic turf in landscape applications. It has been specifically designed to provide instant bond and instant utilization for decorative synthetic turf installations. *Mapecontact LT* has a durable backing and is suitable for all weather conditions.

FEATURES AND BENEFITS

- Instant use; permits immediate foot traffic
- Resistant to high moisture
- Durable, non-stretch backing
- Split-backed liner for easy installation

WHERE TO USE

- Interior and exterior landscape synthetic turf applications
- Approved for cushion and felt-backed synthetic turf backings, low-profile and putting-green-style synthetic turf backings, and other smooth-backed landscape synthetic turf

LIMITATIONS

- Install only in areas recommended by the turf manufacturer.
- Do not use with synthetic turf for sports applications.
- Do not install over wet substrates with standing water.

SUITABLE SUBSTRATES

- Base specified by the turf manufacturer for compaction and drainage
- Underlayment mat approved by the synthetic turf manufacturer

Consult MAPEI's Technical Services Department for installation recommendations regarding substrates and conditions not listed.

SURFACE PREPARATION

- All substrates must be prepared in accordance with the synthetic turf manufacturer for the type of intended use and must comply with current regulations and industry standards.
- All substrates must be structurally sound, dry, solid and stable.
- All surfaces must be level, even, flat and smooth.

PRODUCT APPLICATION

Read all installation instructions thoroughly before installation. Install turf in strict accordance with the turf manufacturer's written instructions.

1. Unroll and acclimate synthetic turf per the manufacturer's written instructions to allow for reduction of internal tensions caused by packaging and transport.
2. Begin by placing *Mapecontact LT* at the start of the seam.
3. Unroll enough *Mapecontact LT* to reach the end of the seam and lay into place, cutting off the excess with a utility knife.
4. Peel off one side of the release liner to expose the adhesive. Carefully place the turf into the exposed side of the tape, making sure to avoid trapping air and avoid wrinkling. Take care to place turf in the proper position because of the extreme difficulty of repositioning once turf is bonded to *Mapecontact LT*.
5. Continue to peel off the other side of release liner and install the alternate side of the turf seam in the same manner.
6. If needed, place weight on the turf seams or roll with 100-lb. (45.4-kg) roller to ensure proper bonding.

Shelf Life and Product Characteristics

Shelf life	1 year when stored in original, unopened packaging at 73°F (23°C)
Storage conditions	50°F to 90°F (10°C to 32°C)
Color	White
VOCs (Rule #1168 of California's SCAQMD)	Adhesive tape is exempt from SCAQMD Rule #1168

Packaging and Coverage

Size	Coverage
Roll: 6" x 50 ft. (15 cm x 15.2 m)	25 sq. ft. (2.32 m ²)

ADDITIONAL INFORMATION

For information on MAPEI's commitment to sustainability and transparency, as well as how MAPEI products may contribute to green building standards and certification systems, contact sustainability_USA@mapei.com (USA) or sustainability-durabilite@mapei.com (Canada).

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement nor replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

CONTACT INFORMATION

MAPEI Headquarters of North America

1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) / (954) 246-8888

Technical Services

U.S. and Puerto Rico:
Flooring: 1-800-992-6273
Concrete and heavy construction: 1-888-365-0614
Canada:
1-800-361-9309

Customer Service

1-800-42-MAPEI (1-800-426-2734)

Edition Date: May 23, 2023 MK 3000257 (23-1137)

For the most current product data and BEST-BACKEDSM warranty information, visit www.mapei.com.
All Rights Reserved. © 2023 MAPEI Corporation.

