



Walk
with
confidence.

Product Information

Commercial Textured E Insert

Product Code:	6800E
Product Family:	CORE Vinyl Inserts
Manufacturer:	GRIP-RITE CARPET ACCESSORIES LTD. 12002 75 ST NW EDMONTON, AB T5B 2B6
Contact Info:	Toll-Free Ph: 800-732-8289 Web: coreflooring.ca
Origin:	Made in Canada with some imported components.
Section:	09 65 00 Resilient Flooring
Related Section:	09 68 00 Carpeting
Usage:	Embossed heavy duty insert for unequal height flooring transition.
Physical Char:	Solid Flexible Thermoplastic Vinyl in Solid Colours; Embossed surface
Dimensions:	Refer to Profile for dimensions
Packaging:	12 Pieces per 3.03" x 149" Tube
Colour Selection:	All colours as per website or official brochure.
DSH:	Store in original packaging until required for use.
Conditions:	Install after all other finishing operations are complete, using the Installation Guide produced specifically for this Product.
Warranty:	Limited 1 Year Warranty. See below for details.
2-2-A Material:	Thermoplastic Vinyl
2-2-B Physical Prop:	Solid, Flexible, Resilient.
2-2-B-1 Recy Cont:	None.
2-2-B-2 Density:	1.38 g/cm ³
2-2-B-3 Hardness:	75 Shore A
2-2-B-6 Flame Spr Ind:	ASTM E 84, Class B
2-2-B-7 MRM:	Resistant.
2-2-B-8 Flexibility:	Will not crack, break, or show signs of fatigue under normal use.
2-2-B-9 Direct Grade:	Allowed.
2-2-B-10 Direct Masonry:	Allowed.

2-2-B-11 Thermodynamic:	Not meant to be stretched.
2-2-B-12 Heat Forming:	Not Recommended.
2-2-B-13 Loading:	Not load-bearing.
2-2-B-14 Paintability:	Paint adhesion not guaranteed.
2-2-B-15 Colourfastness:	Slight fading can occur over time from UV exposure
2-2-B-16 Environmental:	N/A
2-2-B-17 Flash Point:	N/A
2-2-B-18 Ignition Conditions:	Will burn in a fire.
2-2-B-19 Extinction:	Use appropriate means for surrounding materials.
2-2-B-20 Reactivity:	Chemically Stable.

INSTALLATION INSTRUCTIONS

CORE Vinyl Inserts

<i>Introduction:</i>	CORE Vinyl Inserts are designed to provide an attractive transition where appropriate. 'E'-style provides transitions from one height to another; 'T'-style provides transitions between similar-height flooring products. An extension is available where carpet pile is deep.
<i>Handling and Storage:</i>	Store in original packaging until needed for installation. Site-condition CORE Vinyl Inserts to room temperature (18°C to 24°C) for 24 hours in order to achieve proper bonding of adhesives.
<i>Subfloor Preparation:</i>	Floor should be free of debris and dust - we recommend vacuuming before installation of metal channeling. Install flooring first, bringing flooring material to edge of channel on each side for best finish result.
<i>Product Preparation:</i>	If product has been coiled or twisted, lay flat and allow to relax for 24 hours before installing.
<i>Installation:</i>	<p>Install appropriate metal track first.</p> <p>Trim flooring products to fit over base of track and up to edge of channel. Complete proper installation of flooring products before installation of vinyl insert.</p> <p>Cut vinyl insert to size with an appropriate tool.</p> <p>Gently install insert into channel with a rubber mallet or press into place, taking care to fully install into channel, leaving a smooth, straight appearance.</p> <p>If questions arise that have not been addressed in this document, contact your local CORE Flooring Accessories distributor for assistance or CORE Flooring Customer Service at 1-800-732-8289.</p>

Maintenance Guide

CORE Vinyl Inserts

Regular Maintenance:

Special Instructions:

Warranty

CORE Vinyl

Warranty Details:

CORE FLOORING ACCESSORIES LIMITED WARRANTY - VINYL PRODUCTS

For a period of one (1) year from the date of shipment, Grip-Rite Carpet Accessories Ltd. (Grip-Rite) makes the following warranty, subject to the terms and conditions specified herein, for all CORE Flooring Accessories™ (CORE) thermoplastic vinyl products.

CORE products will conform to the Specifications description, with only such reasonable variations as is acceptable in the trade; it is fit for the ordinary purposes for which the product is used; and it will be adequately packaged and labeled.

Grip-Rite will replace any defective product at no charge if the defect is found prior to installation. If the customer believes the product to be defective after installation, the customer must promptly notify Grip-Rite and permit an inspection of the product. If, upon inspection, Grip-Rite determines the product to be defective, subject to the limitations contained in this warranty, Grip-Rite will replace the defective product at its cost in the affected room or area.

To be eligible for replacement under any of these warranties, the customer must give Grip-Rite written notice of any claimed defect immediately upon learning of the defect and in no event more than 90 days after the claimed defect is discovered. Notice shall be given to Grip-Rite at its Corporate Address of 12002 – 75th Street, Edmonton, Alberta T5B 2B6.

Excluded from Warranty:

These warranties do not apply to the following:

1. The exact matching of shade, colour, or embossing.
2. Any express or implied promise made by any salesman or representative that exceeds the limits of these warranties.
3. Tears, burns, cuts, or other damage due to improper handling, installation, improper use of cleaning agents, or of improper maintenance methods.
4. Labor costs for installation of original or replacement material.
5. Sale of "Seconds", "Off Goods" or other irregular (non-first-quality) flooring materials. With respect to "Seconds" or "Off Goods", such are sold "as is", and Grip-Rite makes no warranties whatsoever, express or implied with respect thereto, including warranties of merchantability or fitness for a particular purpose.
6. Problems caused by moisture, hydrostatic pressure, or alkali in the sub-floor.
7. Problems caused by use, handling, maintenance, or installation that is contrary to Grip-Rite's specifications, recommendations, or instructions.
8. Material installed with obvious defects.
9. Damage to flooring products from high heels, spike heels, pallet jacks, construction carts, motorized traffic, or the moving of furniture.
10. Installation of Grip-Rite products with adhesives other than those recommended by Grip-Rite.
11. Exterior installations. Grip-Rite's products are designed for interior applications only.
12. Fading and/or discoloration resulting from heavy sunlight penetration and

ultraviolet ray exposure from direct or glass-filtered sunlight.

13. Material that is not installed and maintained as recommended by Grip-Rite.

14. Damage to flooring products from pallet jacks, construction carts, motorized traffic, or the moving of furniture.

15. Premature wear and deterioration from furniture, spikes, or skate blade exposure.

16. Differences in colour between products and printed or electronic images.

17. Embossing deviations between product and samples, photography, and printed colour illustrations.