


**PROTERMINAL** are manufactured with the same forms and sections, as well as in the very resistant material, the stainless shiny steel 316/1.4401-V4A, suitable for outdoors and marine environment with much presence of saltiness and considerable atmospheric agents. They are used as protection for the external angles of tiles, in order to separate or to create the separating joints in the pavements, to terminate the finishing of wall coverings, for platforms, stair steps, bathtubs, etc. They guarantee the impeccable work, ensuring considerable aesthetic effect as well. They strengthen the tile edge and prevents from chipping and breakages. Required by new European regulations on safety and accident prevention in public and private places.

## PROTERMINAL

POLISHED STAINLESS STEEL  
AISI 316/1.4404-V4A




POLISHED STAINLESS ST. AISI 316L/1.4404-V4A  
with protective film  
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10 mm



Article	H mm	€/lm	€/Pc
PTACM 06	6		
PTACM 08	8		
PTACM 10	10		
PTACM 125	12,5		

### EXAMPLES OF LAYING




### COLOURS



ACM - Polished stainless steel  
AISI 316L

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



**PROTERMINAL** is a professional edging profile used mainly to join similar or different floor materials (e.g. tiles/tiles - tiles/parquet/marble/granite, etc.) of differing thickness.  
**PROTERMINAL** in brass is also used to protect steps and decking, as a floor edging profile, to cover skirting, decking and worktops and to frame doormats.

## PROTERMINAL

POLISHED, NATURAL, ANTIQUE BRASS and  
BRUSHED



POLISHED BRASS thermo packed  
bar length 2,70 lm - pack. 20 Pcs 54 lm

Article	H mm	€/lm	€/Pc
PTOL 06	6		
PTOL 08	8		
PTOL 10	10		
PTOL 125	12,5		
PTOL 15	15		
PTOL 20	20		
PTOL 25	25		


ANTIQUÉ BRASS thermo packed  
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm	€/lm	€/Pc
PTOB 06	6		
PTOB 08	8		
PTOB 10	10		
PTOB 125	12,5		
PTOB 15	15		
PTOB 20	20		
PTOB 25	25		


BRUSHED BRASS thermo packed  
bar length 2,70 lm - pack. 20 Pcs - 54 lm

Article	H mm	€/lm	€/Pc
PTOS 06	6		
PTOS 08	8		
PTOS 10	10		
PTOS 125	12,5		
PTOS 15	15		
PTOS 20	20		
PTOS 25	25		

### COLOURS





Chrome-plated Brass version page 37



1. Choose the "PROTERMINAL" with the same height as the thickness of the floor/wall covering. 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.

### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



Curve version is also available

© = News 2022

\* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

Prices are referred to whole packs 10% increase for minimum orders of 10 Pcs 20% increase for orders of less than 10 Pcs.