



1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett LinoFloor xf²™ homogeneous linoleum floorcovering, single layer on jute backing with xf²™ surface protection.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** Tarkett LinoFloor xf²™ consists of an homogeneous layer of oxidized linseed oil and natural resins mixed with wood or cork flour, limestone and pigments affixed to a jute backing. The marbled pattern extends evenly throughout the total thickness. Surface has xf²™ treatment for surface protection and reduced maintenance.

1.3.2. **Styles:**

- **Veneto, Lenza, Tonali, Trentino and Mineral**
- Thickness: 2.5 mm (.100")
- xf²™ Surface Protection
- Weight/yd² (/m²): 5.5 lbs (3 kg)
- Packaging - Available in 6' 6" (2 m) wide 65-100 linear feet (20-30 m) per roll.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 2034 – Type 1 performance standards for sheet linoleum floor covering
- 2.2. **Heat Stability by Color Change** (ASTM F1514): $\Delta E \leq 8$
- 2.3. **Light Stability by Color Change** (ASTM F1515): $\Delta E \leq 8$
- 2.4. **Flexibility** (ASTM F 137): Passes
- 2.5. **Chemical Resistance** (ASTM F925): Passes
- 2.6. **Static coefficient of friction** (ASTM D2047): ≥ 0.5 SCOF
- 2.7. **Static Load Limit** (ASTM F970): ≤ 0.005 " residual indentation (150 psi load)
- 2.8. **Flammability** (ASTM E648/CRF): ≥ 0.45 W/cm² (Class 1)
- 2.9. **Smoke Development** (ASTM E662): ≤ 450

3. INSTALLATION

3.1. See LinoFloor xf²™ sheet installation instructions for complete details.

3.2. **Adhesives:**

- **Tarkett 965 Adhesive:**
Coverage:
Porous Substrate: 125-150 sq. ft./gal.
Non-porous Substrate: 125-150 sq. ft./gal.
- **Tarkett 975 Two-Part Polyurethane Adhesive:**
Approximate Coverage:
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 10 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to LinoFloor xf² Linoleum sheet maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkettna.com