

1. PROPRIETARY PRODUCT/MANUFACTURER

- 1.1. **Proprietary Product:** Luxury vinyl floor covering with TopClean XP surface plank style. Suitable for commercial working environments.
- 1.2. **Manufacturer:**
Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com
- 1.3. **Proprietary Product Description:**
- 1.4. **Construction:** Tarkett I.D. Inspiration 55 is constructed on a unique composite structure built with homogeneous polymeric calendared layers with a 22 mil PVC wear layer.
- 1.3.1. **Styles:**
- Product: **I.D. Inspiration 55**
 - Surface Treatment: TopClean XP
 - Wear layer Thickness: 22 mil (0.55 mm)
 - Overall thickness .100" (2.5mm)
 - Sizes:
 - Planks: 6.56" x 39.37" (16.7cm x 100cm)
 - Wide Planks: 7.87" x 48" (19.76cm x 121.91cm)
 - Tiles: 19.68" x 19.68" (50cm x 50cm)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Meets ASTM F 1700, Class III, Type B performance
- 2.2. **Residual Indentation** (ASTM F1914): Passes
- 2.3. **Static coefficient of friction** (ASTM D 2047): ≥ 0.5 SCOF
- 2.4. **Static Load Limit** (ASTM F 970): Passes 250 psi
- 2.5. **Dimensional Stability** (ASTM F 2199): Passes
- 2.6. **Resistance to Heat** (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.7. **Resistance to Light:** (ASTM F 1515): $\Delta\Sigma \leq 8.0$
- 2.8. **Chemical Resistance** (ASTM F 925): Passes
- 2.9. **Flammability** (ASTM E648): Class 1 (≥ 0.45 W/cm²)

3. INSTALLATION

See I.D. Inspiration Luxury Vinyl Plank installation instructions for complete details.

3.1. Adhesives:

- **Tarkett 926 Adhesive:**
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 959 Adhesive:**
Porous Substrate: 150-175 sq. ft. per gallon
Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive:**
Porous & Non-porous Substrate: 250-300 sq. ft. per gallon
- **Tarkett RollSmart Adhesive:**
350 - 400 sq. ft. per gallon
(3/8" Nap Paint Roller used with a paint tray)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to ID Inspiration Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkettna.com

Contact Technical Support at (800) 899-8916 or E-mail: Resilient.TechnicalSupport@tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 10 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.