

Product Specification**960 Cove Base Adhesive****1. PROPRIETARY PRODUCT**

1.1. **Proprietary Product:** Tarkett 960 Cove Base Adhesive

1.2. **Manufacturer:**

Tarkett USA Inc.

Phone: (800) 899-8916

30000 Aurora Rd.

Solon, Ohio 44139

Web: www.tarkettna.com

E-mail: info@tarkett.com

Tech: Ext 9297

Samples: Ext 9299

Fax: (440) 632-8920

1.2.1. **Physical Characteristics:**

- Base – Acrylic Polymer
- Color – Light Tan Paste
- Shelf Life – 1 year at 65° F (18° C) to 85° F (30° C) and when stored in unopened, original container in a dry area.
- Freeze thaw up to 5 cycles at 20° F (-7° C)
- Contains no hazardous or carcinogenic ingredients as defined by OSHA chemicals and meets all federal, state and local air quality regulations.
- SCAQMD Rule 1168 – VOC compliant (<1 g/l)

Coverage	2.5"	300-350 lin. ft./gal.
	4"	200-250 lin. ft./gal.
	6"	100-150 lin. ft./gal.
	30 oz. cartridge	4" - 62 to 75 lin. ft.

2. INSTALLATION

2.1. **General Installation Requirements:**

- Tarkett Finishing Borders/Wall Base and adhesives must be site conditioned at room temperature for a minimum of 48 hours prior to, during, and after installation. Room temperature must be maintained between 65° and 85°F (18° and 30°C) with HVAC system operating. A minimum temperature of 55°F (13°C) must be maintained afterwards. The ambient relative humidity should be between 40% and 60%.
- Walls shall be smooth, flat, permanently dry, clean and free of all foreign material such as dust, paint, grease, oils, and solvents, curing and hardening compounds, sealers, asphalt, and old adhesive residue. Fill all depressions, cracks, and other surface irregularities with a good quality patching compound.

2.2. **Manual:** Refer to Adhesive container label for complete installation details.

3. AVAILABILITY AND COST

3.1. Available through authorized Johnsonite distributors nationwide.

4. TRAFFIC:

- Restrict traffic for 24 hours after installation.
- No heavy traffic, rolling loads or furniture placement for 72 hours after installation.
- Wait 72 hours after installation before performing initial cleaning

5. LIMITED WARRANTY

Adhesive warranty is a "system warranty" covered under the product that is recommended to be installed in conjunction with this adhesive. Refer to Tarkett limited warranty for complete details.

6. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, Safety Data Sheet and other technical data, visit us on the web at www.johnsonite.com or contact Tarkett at (800) 899-8916.