

Product Specification**975 Two-Part Urethane Adhesive****1. PROPRIETARY PRODUCT****1.1. Proprietary Product:** Tarkett 975 Two-Part Urethane Adhesive.

Tarkett USA Inc. 30000 Aurora Rd. Solon, Ohio 44139 Web: www.tarkettna.com E-mail: info@tarkett.com	Phone: (800) 899-8916 Tech: Ext 9297 Samples: Ext 9299 Fax: (440) 632-8920
--	---

1.1.1. Physical Characteristics:

- Johnsonite #975 Two-Part Polyurethane Adhesive is an OSHA Flammability Class IIIB, solvent free, polyurethane adhesive.
- High strength adhesive made for installations over porous and non-porous substrates!
- Contains no hazardous or carcinogenic ingredients as defined by OSHA chemicals and meets all federal, state and local air quality regulations.
- Contributes to LEED Certification (E.Q. 4.1: Low-Emitting Materials: Adhesives and Sealants).

Part A:

SCAQMD Rule 1168 – VOC compliant

SCAQMD Rule 443.1 –

Less than 12 gram VOC per liter of materials Part B:

SCAQMD Rule 1168 – VOC compliant

SCAQMD Rule 443.1 –

Less than 12 gram VOC per liter of materials

1.1.2. Application: Arcade, Inertia, Linoleum Sheet, Replay Sheet and Tile, Rubber Floor Tile, Rubber and Vinyl Stair Treads and Nosing, Training and Triumph.**Porous Floor:** 1/16" x 1/16" x 1/16" V-notch

Coverage 165–200 sq. ft. per gallon.

Non-Porous Floor: 1/16" x 1/16" x 1/16" V-notch

Coverage 165-200 sq. ft. per gallon.

1.1.3. Application: Acczent, Aria Sheet and Tile, Cortina Grande, Cortina Grande SR, Defiant Oil and Grease Resistant Rubber Tile, Gemstone, Granit Acoustiflor, Granit Sheet and Tile, Granit Multisafe, ID Freedom, ID Inspiration, ID Patriot, Melodia Sheet and Tile, Optima Sheet and Tile, Vinyl Feature Strips, Vinyl Mouldings, Safe-T Sheet, Tactile Warning Strips, and Toro SC Sheet.**Porous Floor:** 1/32" 1/16" x 1/32" u-notched

Coverage 225-250 sq. ft. per gallon.

Non-Porous Floor: 1/32" 1/16" x 1/32" u-notch

Coverage 225-250 sq. ft. per gallon.

2. INSTALLATION**2.1. General Installation Requirements:**

- Tarkett/Johnsonite flooring and adhesives must be site

conditioned at room temperature for a minimum of 48 hours prior to, during, and after installation. Room temperature must be maintained between 65° and 85°F (18° and 30°C) with HVAC system operating. A minimum temperature of 55°F (13°C) must be maintained afterwards. The ambient relative humidity should be between 40% and 60%.

- Floors shall be smooth, flat, permanently dry, clean and free of all foreign material such as dust, paint, grease, oils, and solvents, curing and hardening compounds, sealers, asphalt, and old adhesive residue.
- It is essential that moisture tests be taken on all concrete floors regardless of age and grade level. Perform three tests for the first 1000 sq. ft. then one test should be conducted for every 1,000 sq. ft. of flooring and the results not exceed 7 lbs. per 1,000 sq. ft. in 24 hours when tested in accordance with ASTM F 1869 Standard Test method for Measuring Vapor Emission Rate of Concrete Subfloor using Anhydrous Calcium Chloride. Or 85% when tested accordance with ASTM F 2170 Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs using in situ Probes. Surface pH of the concrete must range between 7 and 9. If the tests results exceed the limitations, the installation must not proceed until the problem has been corrected.

2.2. Manual: Refer to Adhesive container label for complete installation details.**3. AVAILABILITY AND COST****3.1.** Available through authorized Tarkett distributors nationwide.**4. Traffic:**

- Restrict traffic for 24 hours after installation.
- No heavy traffic, rolling loads or furniture placement for 72 hours after installation.
- Wait 72 hours after installation before performing initial cleaning

5. LIMITED WARRANTY

Adhesive warranty is a "system warranty" covered under the product that is recommended to be installed in conjunction with this adhesive. Refer to Tarkett limited warranty for complete details.

TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, Safety Data Sheet and other technical data, visit us on the web at www.Tarkettna.com or contact Tarkett at (800) 899-8916.