



ADHESIVES

SpraySmart™ 901

Resilient Flooring Spray Adhesive

Standard Plus Homogeneous Sheet

SpraySmart™ 901

SpraySmart 901 is a solvent-free adhesive specifically formulated for installing the following Johnsonite® VCT, VET, SVT, Vinyl Sheet, Rubber Tile products and Finishing Accessories:

- | | | | |
|--|--|--|--|
| VCT <ul style="list-style-type: none"> • Azrock™ VCT (Solids & Feature Strips) • Textile™ VCT • VCT Basketball Kit | VET-SVT <ul style="list-style-type: none"> • Azterra™ • Color Essence™ • Color Essence SR™ • Gemstone™ • Cortina Grande™ • Cortina Grande SR™ • Karim Kolors • Karim Shapes | Vinyl Sheet <ul style="list-style-type: none"> • Acczent® • Acczent® Flourish • Acczent® Wood Acoustiflor® • Acczent® Wood Safe-T • Aria™ • iQ™ Granit™ • iQ™ Granit™ Safe-T • iQ™ Granit™ Micro • Marbled Safe-T • Melodia™ • iQ™ Natural • iQ™ Optima® • iQ™ Optima® Acoustiflor® • Standard Plus | Rubber Tile* <ul style="list-style-type: none"> • Circulinity™ Collection • Defiant™ • Folio™ Collection • Inertia™ • Mesto™ • Mesto Configurations™ • MicroTone™ • Minerality™ • Prima® Marbleized & Olio® • Triumph • Replay® Tile & Sheet |
|--|--|--|--|

* Not approved for Eco-Shell™ with Cork, CorkTones™ or Metallurgy™ at this time

SpraySmart 901 uses an advanced spray adhesive technology that promotes improved productivity and indoor air quality, and provides occupational health and safety benefits. A unique water-based acrylic adhesive, SpraySmart 901 is available in easy-to-use, fully recyclable spray cans which utilize a safe, non-ozone depleting propellant.

SpraySmart 901 is an environmentally friendly, non-toxic, non-flammable intelligent adhesive option, enabling immediate occupancy; an important benefit for healthcare, education, retail and other environments where immediate foot and rolling traffic are required.

Technical Data	Standards	SpraySmart 901 Flooring Adhesive
Adhesive Type		Water-based Acrylic Blend
Appearance		Light Blue
Odor		Sweet Mild Odor
Flash Point		> 212° F
NFPA 704 Flammability Rating		0 - Non-flammable
Storage		Store Between 50° F & 120° F
Shelf Life		2 Years (If unopened)
Open Time		25-45 Minutes
Working Time		2 Hours
VOC Content		< 0.0 g/ml Calculated
Foot Traffic Permitted		Immediately After Installation
Heavy Rolling Traffic Permitted		Immediately After Installation
pH Tolerance	ASTM F710	11 pH
Substrate Moisture Tolerance	ASTM F2170 ASTM F1869	90% RH 8 lbs. per 1,000 ft.2 / 24 hrs.
Underfloor Heating Systems		Yes
Please visit www.tarkettna.com for the most updated specifications and installation, cleaning and maintenance instructions.		

Sustainability Facts

To learn more, visit www.tarkettna.com.

SpraySmart 901	LEED Credits Contribution
Construction Waste Management ReStart® Reclamation Program MR 2	1-2
Material Reuse Supports Reuse & Recycling of Flooring MR 3	1-2
Regional Materials Manufactured in Dalton, GA - an ISO 9001 Facility MR 5	1-2
People-Friendly Spaces Low-emitting Materials IEQ 4.1 Adhesives, FloorScore™ Certified & Meets CA 01350	1
Return On Investment Requires Fewer Man Hours to Install	

COVERAGE:

All flooring types listed porous & non-porous surfaces

VCT:

200 sq. ft./22 oz. can;
1,200 sq. ft./carton

VET-SVT:

160 sq. ft./22 oz. can;
960 sq. ft./carton

Vinyl Sheet:

150 sq. ft./22 oz. can;
900 sq. ft./carton

Rubber Tile:

80 sq. ft./22 oz. can;
4800 sq. ft./carton

SpraySmart™

Immediate Traffic After Installation, Including Rolling Loads	✓
For Use Under Hospital Beds	✓
Eliminates Trowel Marks	✓
Heat Weld Immediately	✓
Increased Limits for Moisture and pH	✓
Reduces Adhesive Consumption	✓
Supports Reuse and Recycling of Flooring	✓
Cradle to Cradle - Silver Certification	✓

