



Feature Strips

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Resilient Feature Strips

1.2. Manufacturer:

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. Proprietary Product Description:

1.3.1. Construction: Tarkett Vinyl Feature Strips are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. The product formulation exceeds ASTM E 648 Class 1 Flammability requirements.

Tarkett Vinyl Feature Strips are designed for interior applications only and not recommended for environments where the product will be exposed to animal fats, vegetable oils, or petroleum based materials. (i.e.: commercial kitchens)

1.3.2. Styles:

FS-DW3: 1" (2.54 cm) wide by 1/8" (3.18 mm) thick feature strip with a stipple-like grout textured finish on one side and smooth surface on the other side.

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces
- 2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Tarkett Resilient Moulding installation and maintenance instructions for complete details.

3.2. Adhesives:

- **Tarkett 965 Adhesive Coverage:**
Porous Substrate: 125-150 sq. ft. per gallon
Non-porous Substrate: 150-175 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive Coverage:**
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon
- **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**
Porous & Non-porous Substrate: 150-175 sq. ft. per gallon
- **Tarkett 901 SpraySmart Adhesive Coverage:**
Porous & Non-porous Substrate: 150 sq. ft. per can (900 sq. ft. per carton)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Resilient Moulding Installation & Maintenance Instructions for complete maintenance details.

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation and Maintenance Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com