



Subfloor Leveler System

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. Proprietary Product: Resilient Leveler Strip and Leveler Strip

1.2. Manufacturer:

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarkettna.com

1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Resilient Leveler Strips are manufactured from a homogeneous composition of polyvinyl chloride (PVC), high quality additives, and colorants. The Leveler Strip complies with A.D.A. requirements for change of level and exceeds the slope to rise ratio for Ramps. The formulation exceeds ASTM E 648 Class 1 Flammability requirements. Tarkett Leveler Strips are designed for interior applications only

1.3.2. Styles:

LS-40: 1/4" (6.35 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-B: 3/8" (9.53 mm) to 1/4" (6.35 mm) butt-to reducer tapering across a 6" (15.24 cm) width, extends LS-40 from 1/4" (6.35 mm) to 3/8" (9.53 mm) thickness, increases taper from 12" (30.48 cm) to 18" (45.72 cm)

LS-40-C: 1/2" (12.7 mm) to 3/8" (9.53 mm) butt-to reducer tapering across a 6" (15.24 cm) width. Note: Extends LS-40 with LS-40-B extension from 3/8" (9.53 mm) to 1/2" (12.7 mm) thickness. Increases taper from 18" (45.72 cm) to 24" (60.96 cm).

LS-40-D: 3/8" (9.53 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-E: 1/2" (12.7 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-F: 1/8" (3.175 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-G: 3/4" (19.05 mm) to substrate butt-to reducer tapering across a 12" (30.48 cm) width

LS-40-K: 1/4" (6.35 mm) to substrate butt-to reducer with 1-3/4" (4.4 cm) flat mounting surface for tack strip installation, 12" (30.48 cm) width, tapered across 10-1/4" (26 cm)

1.3.3. Physical Characteristics:

Length: 4 ft. (1.22 m)

Packaging:

LS-40 10 pcs / carton, 40 ft (12.2 m) - 55 lbs (25 kg)/ctn

LS-40 - B 8 pcs / carton, 32 ft (9.75 m) - 46 lbs. (21 kg)/ctn

LS-40 - C 6 pcs / carton, 24 ft (7.32 m) - 45 lbs. (20 kg)/ctn

LS-40 - D 5 pcs / carton, 20 ft (6.10 m) - 42 lbs. (19 kg)/ctn

LS-40 - E 5 pcs / carton, 20 ft. (6.10 m) - 59 lbs. (27 kg)/ctn

LS-40 - F 20 pcs / carton, 80 ft (24.4 m) - 40 lbs. (18 kg)/ctn

LS-40 - G 4 pcs / carton, 16 ft (4.88 m) - 54 lbs. (25 kg)/ctn

LS-40 - K 10 pcs / carton, 40 ft (12.2 m) - 46 lbs. (21 kg)/ctn

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Slip Resistance:** ASTM D 2047 - Exceeds Federal Standards and ADA recommendations of .5 for flat surfaces

2.2. **Fire Resistance:** ASTM E 648/NFPA 253 (Critical Radiant Flux) - Class 1

3. INSTALLATION

3.1. See Tarkett Subfloor Leveler System installation instructions for complete details.

3.2. Adhesives:

- **Tarkett 925 Adhesive:**

Coverage:

Porous Substrate: 250-300 sq. ft./gal.

Non-porous Substrate: 250-300 sq. ft. per gallon

- **Tarkett 965 Adhesive Coverage:**

Porous Substrate: 125-150 sq. ft. per gallon

Non-porous Substrate: 150-175 sq. ft. per gallon

- **Tarkett 901 SpraySmart Adhesive Coverage:**

Porous & Non-porous Substrate: 80 sq. ft. per can (480 sq. ft. per carton)

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. WARRANTY

Limited 2 year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

6. MAINTENANCE

N/A

7. TECHNICAL SERVICES

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

For current Installation Instructions, Product Specifications, and other technical data, visit us on the web at www.tarkettna.com or contact Tarkett at 1-800-899-8916.

Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

800.899.8916 Ext. 9297 Fax 440.632.5643

info@tarkettna.com

www.tarkettna.com



7.1.1.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916 Ext. 9297 Fax 440.632.5643
info@tarkettna.com

www.tarkettna.com