



1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** SureStart underlayment combines fast install to reduce labor time, provide acoustic sound reduction and moisture impermeability performance.

Note: SureStart is not recommended for use with heavy rolling loads.

1.2. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com

1.3. **Proprietary Product Description:**

1.3.1. **Construction:** High-density synthetic rubber construction with superior acoustical sound reduction performance. SureStart can be specified under Adaptt, Contour, Event+, and ID Latitude collections.

NOTE: SureStart is NOT recommended for use under Collective Pursuit.

1.3.2. **Styles/Sizes:**

SureStart 36" (91.44 cm) wide Underlayment roll	
Product Number:	500033006
UPC:	033799334421
Width/Length:	36" x 33.33' (91.44 x 10.14 m)
Coverage per roll:	100 ft ² / 11.11 yd ² (9.2903 m ²)
Weight per roll:	29 lbs. (13.15 kg)

SureStart 54" (137.16 cm) wide Underlayment roll	
Product Number:	500033007
UPC:	033799334438
Width/Length:	54" x 44.4' (137.16 cm x 13.533 m)
Coverage per roll:	200 ft ² / 22.22 yd ² (9.2903 m ²)
Weight per roll:	58 lbs. (26.30 kg)

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. Density: 62 lbs./ft³ or 42 oz./yd²
- 2.2. Thickness: 0.056"
- 2.3. R-Value: 0.02
- 2.4. Permeability (ASTM E96): < 1 perm
- 2.5. Color: Green
- 2.6. Castor Durability Test: Passes 25,000 cycles
- 2.7. Acoustical (ASTM E2179): ΔIIC 17 (Tested over 6 inch concrete)

3. INSTALLATION

- Concrete must not exceed 99% RH in accordance with ASTM F2170, or 10 lbs. MVER in accordance with ASTM F1869, and pH between 7 to 11.
- See Tarkett SureStart installation instructions for complete details.

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented. Refer to the applicable Tarkett flooring Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical support at (800)-899-8916 or Email: Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. WARRANTY

Limited 10-year Light Commercial Warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com