

**Description**

This brush grade, high performance solvent based, contact adhesive has been formulated to provide aggressive immediate tack and high initial bond strength. Bonded assemblies display immediate high strength characteristics.

**Recommended Use**

Countertops manufacturing, vinyl decking and many others materials.

**Technical specifications**

Color	neutral tan
Viscosity 25°C	800 - 1200 cps
Solids content	22 - 25 %
Specific gravity	0.79

**Operating conditions**

Surfaces must be clean, dry and exempt of dust, grease or other greasy contaminants.

1. Brush adhesive onto both surfaces to be bonded.
2. Allow to dry 1-2 minutes or until the adhesive does not transfer to the finger when firmly pressed.
3. Bond the coated surfaces together with hand or roller.

Note: The adhesive can be heat or solvent reactivated after the solvent has evaporated

**Clean up**

Tools and equipment should be cleaned immediately after use with our S0001

**Precautions**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

**Shelf life / Storage conditions**

12 months. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Environmental impact

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Product code

C2621081941

**DISCLAIMER** The information provided is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. While the information contained herein is believed to be reliable, no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for a particular application or the results to be obtained herefrom. Tri-Texco Inc. cannot guarantee how any products associated with this information will perform in combination with other substances or in the User's process. Due to variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the information or products for the applications disclosed. Tri-Texco Inc. shall not be liable and the User assumes all risk and responsibility for any use or handling of any material beyond Tri-Texco Inc.'s direct control. TRI-TEXCO INC. MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. It is the User's sole responsibility to determine if there are any issues relating to patent infringement of any component or combination of components relating to the supplied information. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner. Because of possible changes in the laws and regulations, as well as possible changes in our products, we cannot guarantee that the status of this product will remain unchanged. Therefore, we recommend that customers continuing to use this product verify its status periodically.

For more information, please consult our safety data sheet or consult our technical service department.



1001 boulevard Industriel, Saint-Eustache, Qc, Canada J7R 6C3  
Sans frais : 1-800-363-2660 Tél.: 450-974-1001 Téléc.: 450-974-0162  
Courriel : [info@tritex.com](mailto:info@tritex.com)

