

# Tuscan Sandstone Heavy Commercial Traffic



**Size**  
12" x 24" nominal (31 cm x 62 cm)  
2.5 mm thick

**Wear Layer**  
20 mil / UV-Cured Urethane

**Edge Treatment**  
Four-Sided Microbevel

**Product Classification**  
ASTM F1700 Class III, Type B

**Installation**  
Full Spread Adhesive  
NEXT 1200™ recommended

**Coordinating Moldings**  
See [nextfloor.net](http://nextfloor.net) for more details.

**Packaging**  
21 pieces per carton (39 lbs)  
42 SF per carton  
54 cartons per pallet  
20 pallets per container

**Testing**

Critical Radiant Flux	ASTM E648	Class I
Surface Flammability	DOC FF 1-70	Passed
Coefficient of Friction	ASTM 2047	Passes > 0.6
Static Load Limit	ASTM F970	1300 lbs
Sound Transmission Class (STC)	ASTM E492	64
Impact Isulation Class (IIC)	ASTM E989	69
High Frequency Impact Isulation Class (HIIC)	ASTM E3222	89

Floor Score Certified  
Phthalate Free  
100% Virgin PVC



**Warranties**  
Lifetime Waterproof  
Lifetime Residential Wear  
25-Year Commercial Wear  
See full warranty text at [nextfloor.net](http://nextfloor.net)

## Sample SKUs

**Handle Boards**  
HB446NF  
5 per carton (50 lbs)

**Strap Sets**  
SS446NF  
5 per carton (45 lbs)

**Folders**  
3P446NF  
\*Includes Invincible Carpet  
20 per cartons (50 lbs)