

PRODUCT SPECIFICATION VINYL CLICK RIGID SPC

COLLECTION	AQUILA Rigid Vinyl Flooring
INVENTORY STYLE #	SPC Vinyl Plank
STYLE NAME(s)	LUXURY VINYL TILE AND PLANK
SELLING STYLE #(s)	FVCVR__
TOTAL # SKU'S (COLORS)	5



PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS

DETAILS

Thickness	5.5 mm (4.5 MM CORE + 1.0 mm EVA Blue Pad)
Wear Layer	20 mil (0.5 mm)
CORE	Extruded composite rigid core
Finish / Coating	SUPER MATTE UV Urethane coating
Nominal Dimensions (inches)	7" width x 48" length x 1/5" thick
Actual Dimensions (inches & mm)	178 mm x 1220 mm (7" x 48")
Pattern Repeat (measurement / # of pieces)	Various 10
Edge Beveled	4 sided Painted Bevel
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)
Backing Class	Residential Grade
Gloss Level (if known)	Matte
Commercial Traffic	Moderate , 10 Year
Texture	Random Embossed in Register
FloorScore Certified (Y/N)	Yes
Lock System	Angle Tap

PACKAGING SPEC'S

Pallet Dimensions (LxWxH)	1200 x 1000 x 1200 (mm)
Square feet per plank/tile [formula field]	2.21
Square feet per carton	23.77
Square feet per pallet	1,189
Square feet per container [formula field]	23,770
Weight per plank/tile (lbs/plank)	4.60
Weight per carton (lbs)	46.00
Weight per pallet (lbs)	1,782
Weight per container (lbs)	44000
Weight per sq ft (lbs) [formula field]	1.85
Pieces per box	10
Boxes per pallet	50
Box Type	Retail carton
Pallets per container	20
Boxes per container	1000

PRODUCT PERFORMANCE / TESTING

ASTM F2055 Size and Tolerance	Passes
ASTM F386 Thickness	Passes
ASTM F2055 Squareness	Passes
ASTM F1914 Residual Indentation	Passes
ASTM F137 Flexibility	Passes
ASTM F2199 Dimensional Stability	0.0038 in./lin. ft.
ASTM F925 Chemical Resistance	Passes
ASTM F1514 Resistance to Heat	Passes
ASTM F1515 Resistance to Light	Passes
ASTM E648 Critical Radiant Flux	Passes
ASTM E662 Optical Smoke Density	Passes
ASTM C1028 Slip Resistance	Passes
ASTM F970 Static Load	750 psi

TECHNICAL INFORMATION / DOCUMENTS

Product Warranty	Lifetime Limited Residential / 10 year Limited Commercial
WARRANTY DOCUMENT*	<i>on line and in Box</i>
INSTALLATION DOCUMENT*	<i>on line and in Box</i>
Installation Method	Floating Lock assembly , Angle Tap (option full glue down)
Approved Installation Methods	Above, Below, and On Grade

PRODUCT CARE DOCUMENT*


Polish Required (Y/N)	NO
Sound Transmission Class (STC)	<i>up to 73 *</i>
Impact Insulation Class (IIC)	<i>up to 72 *</i>



Vision



Nurture



Fearless



Beauty



Focus