

CURATE

| | |
|--|------------------------|
| COLLECTION NAME [IF APPLICABLE] | Curate SPC Vinyl Plank |
| INVENTORY STYLE # | |
| STYLE NAME(s) | |
| SELLING STYLE #(s) | |
| TOTAL # SKU'S (COLORS) | 8 |



| PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS | DETAILS | ADDITIONAL INFORMATION |
|---|--|--|
| Thickness | 7.0 mm | |
| Wear Layer | 0.55 mm | |
| Glass Fiber | n/a | |
| Finish / Coating | UV cured | |
| Nominal Dimensions (inches) | 9" x 60" | |
| Actual Dimensions (inches & mm) | 9" x 60" (229X1524mm) | |
| Pattern Repeat (measurement / # of pieces) | 4 | |
| Paint-Beveled | Yes | |
| Class / ASTM F1700 | Class III Printed Film Vinyl Plank - Type B (embossed) | |
| Backing Class | | |
| Gloss Level (if known) | 2-6° | |
| Commercial Traffic | Heavy | |
| Added Antimicrobial | Yes | |
| FloorScore Certified (Y/N) | Yes | |
| Backstamp Info | YES | Taiga logo on 1.5 mm Acoustic IXPE Pad |
| CE Certification | Yes | |
| Recycled Content | Zero | |

| PACKAGING SPEC'S | DETAILS | ADDITIONAL INFORMATION |
|--|-----------------|------------------------|
| Pallet Dimensions (LxWxH) | 1600x1000x700mm | |
| Square feet per plank [formula field] | 3.75 ft2 | |
| Square feet per carton (plank) | 22.54 ft2 | |
| Square feet per pallet (plank) | 1081.92 ft2 | |
| Square feet per 40' container (plank) | 23802 ft2 | |
| Weight per plank/tile (lbs) | 8.3lbs | |
| Weight per carton (lbs) (plank) | 50.82 | |
| Weight per pallet (lbs) (plank) | 2439 lbs | |
| Weight per 40' container (lbs) (plank) | 53665 lbs | |
| Weight per sq ft (lbs) | 2.26lbs | |
| Pieces per box (plank) | 6 | |
| Boxes per pallet (plank) | 48 | |
| Box Type | cardboard | |
| Pallets per container | 22 | |
| Boxes per container [formula field] | 1200 | |
| Acoustic Pad attached Thickness | 1.5 mm IXPE | |

| PRODUCT PERFORMANCE / TESTING | PERFORMANCE | ASTM REQUIREMENT |
|----------------------------------|-------------|---|
| ASTM F2055 Size and Tolerance | Pass | As specified 0.016 in./lin. ft. |
| ASTM F386 Thickness | Pass | As specified 0.005 in. lin. ft. |
| ASTM F2055 Squareness | Pass | Max. 0.010 in. |
| ASTM F1914 Residual Indentation | Pass | Avg. < 8% |
| ASTM F137 Flexibility | | 1 in (25.4mm) mandrel/no crack or break |
| ASTM F2199 Dimensional Stability | Pass | < 0.020 in./ft. |
| ASTM F925 Chemical Resistance | Pass | No Change/Slight Change |
| ASTM F1514 Resistance to Heat | Pass | < 8 (delta E) avg. |
| ASTM F1515 Resistance to Light | Pass | < 8 (delta E) avg. |
| ASTM E648 Critical Radiant Flux | Pass | Class 1 (< 0.45 W/cm ²) |
| ASTM E662 Optical Smoke Density | Pass | < 450 |
| ASTM C1028 Slip Resistance | Pass | ADA Compliant (> 0.50) |
| ASTM F970 Static Load | __psi | 250 psi (< 0.005") |

| TECHNICAL INFORMATION / DOCUMENTS | DETAILS | ADDITIONAL INFORMATION |
|-----------------------------------|------------------------------------|------------------------|
| Product Warranty | Limited Lifetime Residential | 73 STC / 73 IIC |
| | Limited 25 Year Limited Commercial | |
| Installation Method | Floating lock system | 5G (drop lock) Valinge |
| Approved Installation Methods | Above, Below, and On Grade | Yes |
| Recommended Adhesive(s) | | |
| Polish Required (Y/N) | NO | |