

CURATE TILE

COLLECTION NAME [IF APPLICABLE]	Curate SPC Vinyl Tile
INVENTORY STYLE #	
STYLE NAME(s)	
SELLING STYLE #(s)	
TOTAL # SKU'S (COLORS)	2



PRODUCT SPECIFICATIONS / CONTENT / CERTIFICATIONS	DETAILS	ADDITIONAL INFORMATION
Thickness	7.0 mm	
Wear Layer	0.55 mm	
Glass Fiber	n/a	
Finish / Coating	UV cured	
Nominal Dimensions (inches)	12x24 "	
Actual Dimensions (inches & mm)	302 x 604 mm	
Pattern Repeat (measurement / # of pieces)	4	
Paint-Beveled	Yes	
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)	
Backing Class		
Gloss Level (if known)	0	
Commercial Traffic	Heavy	
Added Antimicrobial	Yes	
FloorScore Certified (Y/N)	Yes	
Backstamp Info	YES	Taiga logo on 1.5 mm Acoustic IXPE Pad
CE Certification	Yes	
Recycled Content	Zero	
PACKAGING SPEC'S	DETAILS	ADDITIONAL INFORMATION
Pallet Dimensions (LxWxH)	1600x1000x700mm	
Square feet per plank [formula field]	2.003 ft2	
Square feet per carton (plank)	20.03	
Square feet per pallet (plank)	961	
Square feet per 40'container (plank)	24.036	
Weight per plank/tile (lbs)	8.3lbs	
Weight per carton (lbs) (plank)	45lbs	
Weight per pallet (lbs) (plank)	2,160	
Weight per 40'container (lbs) (plank)	54000 lbs	
Weight per sq ft (lbs)	2.25lbs	
Pieces per box (plank)	10	
Boxes per pallet (plank)	48	
Box Type	cardboard	
Pallets per container	25	
Boxes per container [formula field]	1200	
Acoustic Pad attached Thickness	1.5 mm IXPE	
PRODUCT PERFORMANCE / TESTING	PERFORMANCE	ASTM REQUIREMENT
ASTM F2055 Size and Tolerance	Pass	As specified 0.016 in./lin. ft.
ASTM F386 Thickness	Pass	As specified 0.005 in. lin. ft.
ASTM F2055 Squareness	Pass	Max. 0.010 in.
ASTM F1914 Residual Indentation	Pass	Avg. < 8%
ASTM F137 Flexibility		1 in (25.4mm) mandrel/no crack or break
ASTM F2199 Dimensional Stability	Pass	< 0.020 in./ft.
ASTM F925 Chemical Resistance	Pass	No Change/Slight Change
ASTM F1514 Resistance to Heat	Pass	< 8 (delta E) avg.
ASTM F1515 Resistance to Light	Pass	< 8 (delta E) avg.
ASTM E648 Critical Radiant Flux	Pass	Class 1 (< 0.45 W/cm ²)
ASTM E662 Optical Smoke Density	Pass	< 450
ASTM C1028 Slip Resistance	Pass	ADA Compliant (> 0.50)
ASTM F970 Static Load	__psi	250 psi (< 0.005")
TECHNICAL INFORMATION / DOCUMENTS	DETAILS	ADDITIONAL INFORMATION
Product Warranty	Limited Lifetime Residential	73 STC / 73 IIC
	Limited 25 Year Limited Commercial	
Installation Method	Floating lock system	5G (drop lock) Valinge
Approved Installation Methods	Above, Below, and On Grade	Yes
Recommended Adhesive(s)		
Polish Required (Y/N)	NO	