

PRODUCT SPECIFICATIONS				
Product Dimensions	Overall Thickness	5.0 mm (with 1.0 mm IXPE Pad)		
	Width and Length	182mmW x 1220mmL		
Packaging (Per Carton)		10 Planks	23.90 Sq.Ft.	39.60Lbs
Construction	Top Layers	High Definition Decor Film		
		Enhanced Polyurethane Coating		
		0.3 mm Wear Layer (12 mil)		
	Core	4.0 mm Limestone Composite: min. 65% stone, 0% wood, 100% Virgin Material		
	Density	1900kg/m³±10%		
	Pad	With 1.0 mm IXPE pad		
Installation	Floating Glueless Tap-Down or Glue-Down			
Under Floor Heating	Approved - See installation manual for details.			
Warranty	15 Year Residential			
Test Data				
Static Load	ASTM F970	250PSI		
Heat Exposure Resistance F1700(70°C/6h)	ASTM F2199 EN16511	≤0.10%		
Swelling after submersion	NALFA LF 01-2011	0% Class 4, Heavy Commercial		
Impact Insulation Class	ASTM E492-09	STC Rating = 65 IIC Rating = 65		
Castor Chair Resistance	ISO 4918	Pass		
Fire Rating	ASTM E648/ 662	Class I		
Wear Resistance	EN 13329 method A	Class 34, Heavy Commercial		
F1700	EN 16511	Class 34, Heavy Commercial		
Impact Resistance (Big Ball)	NALFA LF01-2011 EN 16511	Class 4, Heavy Commercial IC3, Class 34, Heavy Commercial		
Impact Resistance (Small Ball)	NALFA LF01-2011	Class 4, Heavy Commercial		
Static coefficient of Friction	ASTM D2047	Dry: 0.38, Wet: 0.9		
Resistance to staining F1700	ASTM F925 NALFA LF01-2011	Pass Class 4, Heavy Commercial		
Chemical Composition				
VOC	FloorScore™	Pass California 01350		
Ortho-phthalates	Prop 65	Not Detected / In Compliance		
Lead	CPSIA	None Detected		
Substances of Very High Concern (SVHC) (Mercury, Chromium VI, Cadmium, SCCp, Benzene, Xylene, Tributyltin, etc.)		Not Detected / REACH Compliant		