

## Quiet Comfort™ Underlayment Options

For your Engineered Wood and/or Laminate Installations:

	S-1836 Laminate	S-1837 Engineered Wood & Laminate	S-1841 Engineered Wood
Sound Barrier	• • • • •	• •	• • •
Moisture Barrier	• • •	• • •	• • • • •
Ease of Install	• • •	• • •	• • • • •

For your LVT and/or Engineered Tile Installations:

	S-1840 LVT, Rigid Core, & Engineered Tile	S-1841 LVT & Engineered Tile
Sound Barrier	• • • • •	• • •
Moisture Barrier	• • •	• • • • •
Ease of Install	• •	• • • • •



Armstrong Flooring provides many options of underlayments that are designed with your environment, flooring product type and installation challenges in mind. They are easy to work with, require less subfloor preparation and enhance the overall floor performance.

	BETTER			BEST	BETTER	BEST
	S-1841 Quiet Comfort™ Floating Underlayment			S-1840 Quiet Comfort™ Floating Underlayment	S-1837 Quiet Comfort™	S-1836 Quiet Comfort™ Premium
	Standard 100 sq. ft. roll FP01841101	Standard 350 sq. ft. roll FPX2411205	Jumbo ~1,600 sq. ft. roll FPX2410205	300 sq. ft. roll FP1840101	Standard 100 sq. ft. roll FP1837121L	300 sq. ft. roll FP1836121T
Key Features & Benefits	Reduces subfloor prep and simplifies installation. Moisture barrier with no RH limit and resists mold and mildew. Reduces through-the-floor and in-room footfall noise.			Built-in moisture barrier and adapts to subfloor irregularities	Most effective moisture barrier with insulating sound absorption	Ultimate protection, durability & noise reduction
Construction	HMC Saturated Polyester			Polypropylene Foam	Closed-cell polyethylene foam laminated to 3 mil polyethylene film	High density cross-linked polyethylene foam laminated to 3 mil polyethylene film
Gauge	0.02" (0.5 mm)			0.039" (1 mm)	0.075" (1.095 mm)	0.075" (1.095 mm)
STC/IIC*	62/57			62/64	51/53	68/63
Color	Gray			Black	White foam on black film	White foam on black film
Dimensions (WxL)	6' x 16.7'	6' x 58.3'	6' x 225'	6' x 50'	48" x 25"	48" x 25"
Suitable for products	For use with Engineered wood, LVT & Engineered Tile			For use with LVT, Rigid Core, & Engineered Tile	For use with Laminate and Engineered Wood	For use with Laminate

These products are not subject to the newly imposed tariffs.



\*The ASTM tests for determining STC and IIC values do not specify a standard floor-ceiling structure for conducting the tests. The floor-ceiling structure used for the tests should be considered when comparing STC and IIC values of competitive products. Refer to FloorExpert.com for more information.

F-10278-1018 Armstrong and the Armstrong logo are trademarks of AWI Licensing LLC. All other trademarks are owned by Armstrong Flooring, Inc. or its subsidiaries. © 2018 AFI Licensing LLC.