





**HARDWOOD FLOORING -
SOLID CONSTRUCTION**

Lauzon prefinished solid hardwood flooring is unmatched for its extraordinary beauty and timeless elegance. The precise milling and expert craftsmanship of a Lauzon solid hardwood floor will ensure problem-free installation when installed on and above grade level.

VALIDATED ECO-DECLARATION

Product's contribution to LEED[®] v4

©Copyright 2016 by Vertima inc.

PRODUCT SPECIFICATIONS	ENVIRONMENTAL IMPACTS	TECHNICAL PERFORMANCES
<p>Reference Hardwood flooring - solid construction</p> <p>Final manufacturing locations St-Norbert, Quebec J0K 3C0 CANADA Maniwaki, Quebec J9E 1N8 CANADA</p> <p>Composition Dry solid sawn hardwood and finishes</p>	<p>Life Cycle Assessment -</p> <p>Product's carbon footprint -</p> <p>Environmental Product Declaration Industry-wide (generic) (September 2019 to September 2024) ISO 14025:2006, Type III</p>	<p>Performance tests Tests performed by Lauzon Flooring according to ASTM standards</p> <p>Expected life lifelong (Depending on usage)</p>
ATTRIBUTES	INGREDIENTS AND EMISSIONS	MANUFACTURER'S ENVIRONMENTAL MANAGEMENT
<p>Recycled content Pre-consumer: 0% Post-consumer: 0%</p> <p>Regional content The extraction location has been documented for 99.0% of raw materials used in manufacturing the final product, based on a weight ratio.</p> <p>FSC Certification SAI-COC-003198 (When specified)</p> <p>Rapidly renewable materials -</p> <p>Biobased materials -</p>	<p>Declaration of chemical ingredients 1,000ppm</p> <p>Type of declaration HPD[®] version 2.1.1 Health Product Declaration[®]</p> <p>Emission test CDPH</p> <p>VOCs Depending on finishes type (factory applied) -</p> <p>Formaldehyde -</p> <p>Others Pure Genius, ACTIO₂[™] technology</p>	<p>ISO 14001 Certification CERT-0083536</p> <p>Extended Producer Responsibility (Take Back Program) -</p> <p>Corporate Sustainability Reporting (CSR : GRI, ISO 26000, BNQ 21000 or other) -</p>
		CERTIFICATIONS AND CONFORMITY REPORTS
		<p> The mark of responsible forestry FSC[®] C143353</p> <p> Lacey Act Compliant</p> <p>PURE GENIUS[®] AIR-PURIFYING SMART FLOOR</p>

Since 1985, we are committed to marrying the artistry of finely crafted wood with new technologies to offer you resilient, naturally comfortable and – equally important – comforting floors. It's unique business model, scale, know-how and commitment to responsibly managing its resources, that's what makes Lauzon such a special brand.

2101 Côte des Cascades, Papineauville, Quebec J0V 1R0 CANADA
www.plancherslauzon.com

Master Format[®]: **09 64 29**
Validated Eco-Declaration:
VED16-1067-01
Original issue date: **2016/05**
Changes made on : **2019/09/11**
Period of validity: **2019/11 to 2020/11**



ENVIRONMENTAL DATA SHEET

HARDWOOD FLOORING - SOLID CONSTRUCTION



- Precision milling
- Available in many species
- Available in sizes: 2 1/4", 3 1/4" and 4 1/4"

ATTRIBUTES

RECYCLED CONTENT

Hardwood Flooring - solid construction	Weight ratio	Pre-consumer	Post-consumer
2 1/4", 3 1/4" and 4 1/4"	100%	0%	0%

Validated Eco-Declaration - Recycled Content

Methodology: on-site audit, supply chain evaluation, analysis and validation of the recycled content data according to the weight ratio of each of the components used in manufacturing the final product.

Vertima's procedure: VERT-032008-01, First Edition.

REGIONAL CONTENT

Weight ratio	Final manufacturing locations
100%	St-Norbert, Quebec J0K 3C0 CANADA Maniwaki, Quebec J9E 1N8 CANADA

Validated Eco-Declaration - Regional Content

Methodology: on-site audit, supply chain evaluation, analysis and validation of the regional content data according to the weight ratio of each of the components used in manufacturing the final product.

Vertima's procedure: VERT-032008-02, First Edition.

Product components	Weight ratio	Extraction locations	Transportation
Dry solid sawn hardwood	99.0%	Canada and US	Road
Finishes	< 1%	N/A	N/A

*The extraction locations have been documented for 99.0% of materials of the final product components, based on weight ratio.



ATTRIBUTES (CONTINUED)

REGIONAL CONTENT (CONTINUED)



1. HARVEST LOCATION OF HARDWOOD: (Details available upon request)

Canada: Quebec and Ontario

United States: Connecticut, Massachusetts, New Hampshire, New York, Vermont and Maine

2. HARVEST LOCATION OF TROPICAL HARDWOOD: (Details available upon request)

Brazil: Brazilian Cherry

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

Validated Eco-Declaration:
VED16-1067-01
Period of validity:
2019/11 to 2020/11



ENVIRONMENTAL DATA SHEET


HARDWOOD FLOORING - SOLID CONSTRUCTION



ATTRIBUTES (CONTINUED)

FSC® CERTIFICATION

FSC®-certified Lauzon Solid hardwood flooring are available for the following wood species: **Hard Maple, Beech, Red Oak and Yellow Birch.** (When specified)

	Hardwood flooring - Solid construction	% Wood component	% FSC®-certified wood	% calculated according to total weight of wood components used in the product final assembly versus the total weight of FSC®-Certified wood
	Wood	99.0%	99.0%	100%
	Lauzon Flooring	FSC Code	Type of certification	Period of validity
	St-Norbert and Maniwaki Quebec, Canada	FSC-C143353	Multisite, FSC® MIX	2018/09/12 to 2023/09/10

Validated Eco-Declaration—FSC® Certification
 Methodology: on-site audit, supply chain evaluation and validation of FSC® certification documents confirming the type of certification and calculation, based on weight ratio, of the wood that is FSC®-certified in the final product.
 Vertima's procedure: VERT-032008-03, First Edition.

ENVIRONMENTAL IMPACTS

ENVIRONMENTAL PRODUCT DECLARATION (EPD) Industry-wide (generic) ISO 14025:2006, Type III

In 2011, Lauzon collaborated to a life-cycle analysis to implement a generic Environmental Product Declaration for all production of hardwood floors in Eastern Canada. This approach was carried out by the owner of the Quebec Wood Export Bureau and audited by the FPInnovations Program Operator.

Product Category Rules	1. FPInnovations (2013) PCR: "North American Structural and Architectural Wood Products", version 1.1 2. NSF National Center for Sustainability Standards (2014) PCR for Flooring: Resilient, Laminate, Ceramic, Wood"
------------------------	---

Functional unit	Scope of LCA	Expected life time	Valid until
1 m ² of installed flooring	Cradle to Grave	25 years (According to the referenced PCR)	August 2014 to August 2019

Table 1. Life cycle environmental performance

Impact Category	Unit	Per 1 m ² of flooring	Per 10 ft ² of flooring
Global warming potential	kg CO ₂ eq	-2.29	-2.13
Ozone depletion potential	kg CFC-11 eq	4,67E-08	4,34E-03
Smog creation potential	kg O ₃ eq	1.53	1.42
Acidification potential	kg SO ₂ eq	0.08	0.07
Eutrophication potential	kg N eq	5,27E-03	4,90E-03
Non-renewable, fossil	MJ	160,48	149,09
Non-renewable, nuclear	MJ	19.25	17.88

Source: EPD Report

This EPD encompasses products from multiple manufacturers and represents an average of pre-finished hardwood strip flooring produced in Eastern Canada. This average is based on a sample that included five Eastern Canadian flooring mills and three finishing plants. This data represents about 10% of total Canadian hardwood flooring production in the year 2004.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

Validated Eco-Declaration:
VED16-1067-01
 Period of validity:
2019/11 to 2020/11



ENVIRONMENTAL DATA SHEET

HARDWOOD FLOORING - SOLID CONSTRUCTION



INGREDIENTS AND EMISSIONS

DECLARATION OF CHEMICAL INGREDIENTS



VERSION 2.1

Type of declaration: Health Product Declaration® (HPD®) version 2.1.1

Period of validity: September 04, 2019 to September 04, 2022

The content of Lauzon Flooring's hardwood flooring - solid construction was assessed for health hazard warnings as required using Pharos¹.

HPDC repository URL: <http://www.hpd-collaborative.org/hpd-public-repository>

The Health Product Declaration® and logo is owned by the Health Product Declaration® Collaborative and is used with permission.

Declaration: Prepared by Vertima inc., third party approved by HPDC

Ingredients inventory threshold: 1,000 ppm

Full disclosure of intentional ingredients: No

Full disclosure of known hazards: Yes

Hazard(s) associated with the product ingredients:

This HPD Standard describes a declaration of product content and direct health hazards associated with exposure to its individual contents. The Declaration is not an assessment of risks associated with actual use of the product. It does not address the potential health impacts of substances used or created during manufacture that do not appear in the final product as residuals, nor substances created during combustion or other degradation processes.

Highest concern GreenScreen® Benchmark: Benchmark 1²

- | | | |
|---|---|---|
| <input type="checkbox"/> PBT (Persistent, Bioaccumulative, Toxic) | <input checked="" type="checkbox"/> Respiratory | <input checked="" type="checkbox"/> Physical hazard |
| <input checked="" type="checkbox"/> Cancer | <input type="checkbox"/> Neurotoxicity | <input type="checkbox"/> Global warming |
| <input checked="" type="checkbox"/> Gene mutation | <input checked="" type="checkbox"/> Mammal | <input type="checkbox"/> Ozone depletion |
| <input checked="" type="checkbox"/> Development | <input type="checkbox"/> Land toxicity | <input checked="" type="checkbox"/> Multiple |
| <input checked="" type="checkbox"/> Reproductive | <input type="checkbox"/> Aquatic toxicity | <input checked="" type="checkbox"/> Aquatic |
| <input checked="" type="checkbox"/> Endocrine | <input checked="" type="checkbox"/> Skin or eye | <input type="checkbox"/> Unknow |

¹Pharos Project: Database that provides human and environmental health information of chemicals, materials and building products (<https://www.pharosproject.net>).

²GreenScreen scores (GS) Benchmarks of chemical ingredients: Benchmark 1 (Avoid, chemical of high concern), Benchmark 2 (Use but search for safer substitutes), Benchmark 3 (Use but still opportunity for improvement), Benchmark 4 (Prefer, safer chemical).

TABLE OF INGREDIENTS

Name	Role	CAS ¹	Weight Ratio	GreenScreen ²	Note (s) (for more details refer to the HPD®)
Hardwood	Main material	-	99.4%	Not Screened	Special Condition : BIO
Finish system #1	Alternate Finish	107-21-1 14807-96-6	0.0%-0.6%	BM-1	LT-1, LT-P1, LT-UNK, BM-2 and BM-4 Scores also present
Finish system #2	Alternate Finish	14807-96-6	0.0%-0.6%	BM-1	LT-1, LT-P1, LT-UNK and BM-4 Scores also present
Finish system #3	Alternate Finish	107-21-1 14807-96-6	0.0%-0.6%	BM-1	LT-1, LT-P1, LT-UNK, BM-2 and BM-4 Scores also present
Finish system #4	Alternate Finish	14807-96-6	0.0%-0.6%	BM-1	LT-1, LT-P1, LT-UNK and BM-4 Scores also present
Optional top layer	Air-purifying layer	7732-18-5	0.0%-0.1%	BM-4	-

¹Only the CAS numbers with the score of highest concern are listed.

²GS List Translator (LT) scores of chemical ingredients: LT-1, likely GS Benchmark 1; LT-P1, possible GS Benchmark 1; U-LT or LT-UNK, present on a GS Specified Lists but there is insufficient information to classify the hazard as LT-1 or LT-P1 (does not mean the chemical is safe).

Validated Eco-Declaration—Declaration of Chemical ingredients

Methodology: validation of the documentation confirming the methodology and reporting of chemical ingredients.

Vertima's procedure: VERT-032009-01, First Edition.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

Validated Eco-Declaration:
VED16-1067-01
Period of validity:
2019/11 to 2020/11



INGREDIENTS AND EMISSIONS (CONTINUED)

PURE GENIUS TECHNOLOGY

What is Pure Genius® Technology

PURE GENIUS[®]

AIR-PURIFYING SMART FLOOR

Pure Genius is a light-activated, air-purifying agent made of titanium dioxide, which is integrated into Lauzon's Titanium floor finish. Pure Genius helps improve several ways while bettering air quality:

- Reduces symptoms of respiratory (asthma & allergies) and immunosuppressive disorder;
- Actively suppresses potentially carcinogenic emissions (formaldehyde, solvents, voc's and other air-borne pollutants);
- Decomposes up to 99.6% of bacteria, viruses and mold;
- Reduces stubborn odors (cooking, smoke, pets, etc.);
- Disperses hardwood floor cleaners more easily, giving you cleaner floor.

All these criterias have been tested and validated by independent laboratory, as defined below:

Photocatalytic activity test - NOX removal - ISO 22197-1 standard

Test summary

Under standardized lighting conditions, the Pure Genius sample shows high activity in the degradation of NOX, translating in 7.8 lbs of NOX per year per 454 sq ft of hardwood floor.

Source: Photocat A/S, Roskilde (Danemark) August, 2013

Photocatalytic activity test - Formaldehyde removal - ISO 22197-4 standard

Test summary

In standardized test conditions, a formadehyde degradation index of 28 PPB was obtained, which equals, over the course of a single hour, to the removal of up to 17.5% of formaldehyde.

Source: D-Tox Laboratory , M. Bahnemann Ph. D., Hanovre (Germany) August, 2013

Photocatalytic activity test - Acetaldehyde removal - ISO 22197-42 standard

Test summary

An acetaldehyde degradation index of 400 PPB was obtained in standardized test conditions. Over the course of a single hour, up to 40% of a constant flow of acetaldehyde compound contaminants were removed.

Source: D-Tox Laboratory , M. Bahnemann Ph. D., Hanovre (Germany) December, 2013

Anti-microbial properties - ISO 27447 2009 standard

Test summary

After 8 hours in standardized conditions, Pure Genius had reduced E. coli (ATCC 8739) of 99.65%, S. aureus (ATCC 6538P) of 99.63%, and K.pneumoniae (ATCC 4352) of 99.7%.

Source: Tile Council of North America, US, Report TCNA-684-13 Octobre, 2013

***More details on laboratory tests available from Lauzon Flooring's website.**

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

©Copyright 2016 by Vertima inc.



ENVIRONMENTAL DATA SHEET

SOLID HARDWOOD FLOORING

TECHNICAL PERFORMANCE S

PERFORMANCE TESTS

Tests carried out by Lauzon according to standard are listed below:

- ASTM D3359-02 -Standard Test Methods for Measuring Adhesion by Tape Test;
- ASTM D4060-14 -Standard Test Method for Abrasion Resistance of Organic Coatings by the Taber Abraser;
- NEMA LD 3-2005 - High-Pressure Decorative Laminates;
- ASTM D4442-15 -Standard Test Methods for Direct Moisture Content Measurement of Wood and Wood-Based Materials;
- ASTM D1792 - Standard Test Method for Long-Term Removability Properties of Emulsion Floor Polishes.

EXPECTED LIFE

LIFELONG

(Depending on usage)

WARRANTY

- Limited lifetime structural warranty;
- Aluminium oxide finish, Essential collection (25 years) - residential applications only;
- Titanium finish, Ambiance collection (30 years) - residential applications only;
- Titanium finish, Designer collection (35 years) - residential applications only;
- Five (5)-year light commercial finish limited warranty on Titanium finish.

MANUFACTURER'S MANAGEMENT PROGRAM

CERTIFICATION (ISO 14001:2015)

Environmental Management System

Lauzon Forestry Resources Inc. 175, rue Alexandre, Thurso, Quebec JOX 3B0 CANADA

Certification number	Certification agency	Period of validity
CERT-0105410	SAI Global	Until September, 2020



Validated Eco-declaration - ISO Certification
Methodology: validation of documents attesting the ISO Certification.
Vertima's procedure: VERT-032009-03, First Edition.

MANUFACTURER'S ENVIRONMENTAL MANAGEMENT

COMPANY'S COMMITMENT

At Lauzon, with our vertical integration business model, including our ISO 14001 and Rainforest Alliance certifications, all our FSC[®] certified hardwood floors - such as our Canadian Hard Maple, which boasts one of the shortest carbon trails in the industry, our modern sawmill and our zero waste policy, we aim to do things right from forest to floor. All our floors meet the strictest standards for toxic emissions. With our exclusive Pure Genius[®], we take purity to a whole new level by allowing your floor to purify the air the way trees do. We share your concerns for a greener, healthier planet.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.



ENVIRONMENTAL DATA SHEET

HARDWOOD FLOORING - SOLID CONSTRUCTION

PRODUCT CONTRIBUTION SUMMARY

LEED[®] v4 requirements for Building Design + Construction (BD+C)

New Construction, Core and Shell, School, Retail, Data Centers, Warehouse and Distribution Centers, Hospitality and Healthcare.

LEED[®] v4 requirements for Interior Design + Construction (ID+C)

Commercial Interiors, Retail and Hospitality.

MATERIALS AND RESOURCES		POINTS	PRODUCT CONTRIBUTION
MR	Building Product Disclosure and Optimization – Environmental Product Declarations (EPD) Option 1: Hardwood flooring - solid construction from Lauzon Flooring contributes to this credit due to the availability of an industry-wide (generic) EPD (type III) and is valued as 1/2 whole product out of the 20 needed for purposes of credit achievement calculation.	1 point	ENVIRONMENTAL IMPACTS
			Industry-wide (generic) EPD, Type III
MR	Building Product Disclosure and Optimization – Sourcing of Raw Materials Option 2: Leadership extraction practices May also contribute to the location valuation factor if the product is sourced (extracted, manufactured, purchased) within 160 km of the project site.	1 point	ATTRIBUTES
			FSC [®] - Certified (100%) (When specified, see page 4)
MR	Building Product Disclosure and Optimization – Material Ingredients Option 1: Material ingredients reporting	1 point	INGREDIENTS AND EMISSIONS
			Health Product Declaration [®] HPD [®] Version 2.1.1
INDOOR ENVIRONMENTAL QUALITY		POINTS	PRODUCT CONTRIBUTION
EQ	Low-Emitting Materials Option 1 Product category calculation For the flooring category 100% of flooring must meet the requirements.	Contribute	INGREDIENTS AND EMISSIONS
			The product has been tested in a laboratory in accordance with the CDPH Standard Method v1.2-2017

LEED[®] v4 requirements for Homes

Applies to single family homes, low-rise multi-family (one to three stories), or mid-rise multi-family (four to six stories); includes Homes and Multifamily Lowrise and Multifamily Midrise.

MATERIALS AND RESOURCES		POINTS	PRODUCT CONTRIBUTION
MR Prereq 1	Certified tropical Wood ¹ Tropical wood species from Lauzon Flooring should not be selected during a LEED project for Homes since they are not FSC [®] -Certified.	Prerequisite	ATTRIBUTES
			¹ The tropical wood species from Lauzon Flooring for hardwood flooring - solid construction is Brazilian Cherry
MR Credit 2	Environmentally Preferable Products Option 2: Environmentally Preferable Products ² At least 90% of all materials in each category must meet credit requirements. Hardwood flooring - solid construction from Lauzon contributes to 0.5 point for FSC [®] -Certified.	0.5 point ²	ATTRIBUTES
			FSC [®] -Certified (100%) (When specified, see page 4)
INDOOR ENVIRONMENTAL QUALITY		POINTS	PRODUCT CONTRIBUTION
EQ Credit 7	Low-Emitting Products At least 90% of all materials in each category must meet credit requirements.	Contribute	INGREDIENTS AND EMISSIONS
			The product has been tested in a laboratory in accordance with the CDPH Standard Method v1.2-2017

It is important to consider that the total amount of possible points reflects the number of achievable points in each credit category. The product itself cannot achieve this score, as defined above, but is considered as a beneficial element in order to achieve LEED[®] credits.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

Validated Eco-Declaration:
VED16-1067-01
Period of validity:

2019/11 to 2020/11



ENVIRONMENTAL DATA SHEET

HARDWOOD FLOORING - SOLID CONSTRUCTION

PRODUCT CONTRIBUTION SUMMARY

WELL BUILDING STANDARD[®] v1 (February 2016)

Core and Shell
New and Existing Buildings
New and Existing Interiors

AIR		P - PRECONDITION O - OPTIMIZATION	PRODUCT CONTRIBUTION
04	VOC REDUCTION Part 3: Flooring The VOC content of all newly installed flooring must meet all limits set by the following, as applicable: a. California Department of Public Health (CDPH) Standard Method v1.1-2010.	PRECONDITION The product is compliant	INGREDIENTS AND EMISSIONS Hardwood flooring - Solid construction does contribute because it has not been tested in accordance with the CDPH Standard Method v1.2-2017
	TOXIC MATERIAL REDUCTION Part 2: Flame retardant limitation Halogenated flame retardants are limited in the following components to 0.01% (100 ppm) to the extent allowable by local code: b. Flooring, ceiling tiles and wall coverings.		OPTIMIZATION* The product is compliant
26	ENHANCED MATERIAL SAFETY Part 1: Precautionary material selection At least one of the following requirements is met: a. The project completes all Imperatives in the Materials Petal under the Living Building Challenge 3.0. b. Cradle to Cradle [™] Material Health Certified c. No GreenScreen [®] Benchmark 1, List Translator 1 or List Translator Possible 1 substances over 1,000 ppm, as verified by a qualified Ph.D. toxicologist or Certified Industrial Hygienist. d. Some combination of the certifications described in Requirements b and c.	OPTIMIZATION* The product is not compliant	ATTRIBUTES INGREDIENTS AND EMISSIONS & ENVIRONMENTAL IMPACTS Hardwood flooring - Solid construction does not contribute because it does not meet any of the criteria in the list.
	MATERIAL TRANSPARENCY Part 1: Material information Interior finishes and finish materials, furnishings (including workstations) and built-in furniture have some combination of the following material descriptions: b. Health Product Declaration [®]		OPTIMIZATION* The product is compliant

*OPTIMIZATION NOT APPLICABLE TO THE CORE AND SHELL PROJECT v1 (February 2016)

It is important to consider that the criteria identified in the table reflects each category in which the product must conform to either a Precondition or an Optimization. The product itself does not meet the compliance to achieve as defined above, but is considered a beneficial element in all building components to meet WELL criteria.

Free translation by Vertima Well Building Standard guide.

The data included in this Environmental Data Sheet has been provided by the client and the suppliers, who are responsible for its veracity and the integrity. Vertima follows a rigorous protocol, including an on-site audit of the factory, an audit of the manufacturer's supply chain documentation, and the analysis and validation of all supporting documents. However, Vertima cannot be held responsible for false or misleading information that may cause any loss or damage suffered, in all or in part, caused by errors and omissions relative to the data collection, compilation and/or interpretation. The analysis protocol used by Vertima is available on request.

©Copyright 2016 by Vertima inc.

Validated Eco-Declaration:
VED16-1067-01
 Period of validity:
2019/11 to 2020/11

