

ARDEX CD FINE™

Concrete Dressing

Modified with high-performance polymers and hydraulic cements for exceptional bond strength. Apply by trowel, squeegee or hopper gun; broom texture before it sets for a reduced-slip surface.

Key Features

- Portland cement-based
- Interior or exterior
- For floors and walls
- Special mix ratio for minor patching
- Available in gray and white
- Accepts color for decorative finishes

Installation

- **General priming recommendations:**
 - No priming required
 - Use ARDEX CG™ Concrete Guard 1:1 with water over highly porous surfaces to minimize pinholes
 - Use ARDEX CG Concrete Guard 1:1 with water can increase the working time for ARDEX CD FINE™
- **Packaging:** 20 lb. bag (9 kg)
- **Coverage:** up to 100 sq. ft. per bag at 1/32" (9.3 m² at 0.8 mm)
- **Pot life:** 30 minutes
- **Working time:** approx. 10-15 minutes
- **Walkable:** 2 hours
- **Install waterborne coating:** approx. 2 hours

Performance

- **ASTM C109 (air mod) Compressive Strength:** 4,000 psi (280 kg/cm²) at 28 days
- **VOC:** 0



ENGINEERED CONCRETE
REPAIR SYSTEMS



AMERICAS

+1-724-203-5000
888-512-7339

www.ardexamericas.com

AF411 11/14