

The Professional's Formula For Success™

## HENRY<sub>®</sub> 356C MultiPro™

Premium Commercial Multipurpose Carpet & Sheet Vinyl Adhesive



**Use for:** Carpet backed with jute, Action Bac® (polypropylene), urethane foam, latex foam (rubber), unitary, unitary Action Bac®, hot melt and urethane laminate, as well as woven and non-backed needle-punched carpet. It is also suitable for use with felt-backed sheet flooring, **linoleum**, cork sheet underlayment and indoor/outdoor carpeting (indoor use only).

## **Key Features & Benefits:**

- Extremely Versatile best choice for many applications
- Strong Initial Grab Helps reduce edge curl
- Excellent Rebond Allows for repositioning and last minute adjustments
- Short Open Time for quicker installation

## **Bonds To:**

All grade levels: concrete, well-bonded cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), terrazzo, ceramic tile, marble, certain epoxy coatings and existing, fully adhered, non-cushion backed resilient flooring. Clean and abraded steel, stainless steel, aluminum, lead, copper, brass and bronze.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)

## Coverage:

**Rough-Backed Carpet:** V-Notch 1/8"D x 1/8"W x 1/16"A 90 - 108 sq. ft. / gal.

**Smooth-Backed Carpet:** V-Notch 3/32"D x 3/32"W x 3/32"A 144 - 162 sq. ft. / gal.

**Felt-Backed Sheet Vinyl, Linoleum, Cork Sheet Underlayment:** Sq. Notch 1/16"D x 1/16"W x 1/16"A 140 - 160 sq. ft. / gal.







