## **ARDEX SKM™**

# Skimcoat Patch and Finishing Underlayment

ARDEX SKM™ can be used use over interior concrete, wood, ceramic or quarry tile, cutback and other non-water soluble adhesive residues. ARDEX SKM delivers a permanent, smooth, durable finish prior to the installation of floor coverings. ARDEX SKM hardens quickly, is very easy to apply and dries fast without shrinkage.

## **Key Features**

- Non-sanded for a true featheredge
- Creamy consistency; very easy to apply
- Trowels to a smooth, hard surface that can be easily sanded
- Install floor coverings in as little as 30 minutes

### Installation

• Priming: no priming required

• Coverage: 150-200 sq.ft. at a skimcoat

• **Mixing:** 1.5 quarts (1.4L) water per 10lb (5kg) bag or 3 parts powder 1 part water by volume

• **Thickness:** featherdge up to ½" (12mm)

Pot Life: 15 minutes
Walkable: 30 minutes
Install Floor Coverings:

• Skimcoat: 30 minutes

• 1/16" to 1/2": Tile 60-90 mins. Other floor

coverings 1 to 2 hours

• **VOC**: 0 g/L

#### **Performance**

• **VOC**: 0



Refer to the technical data sheet at www.ardexamericas.com or call 888-512-7339 prior to installation. For free ARDEX product training click on ARDEX Academy.

For easy-to use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.









