

CUSH-N-TRED[®]

ACOUSTICAL

3.5^{MM}

The Affordable Green Choice

- For use with laminate and engineered wood
- Suitable for wall to wall carpet and area rugs
- Participating in the recycling of over 123 M auto tires
- Contributes to LEED[®] green building credits for recycled content, regional materials and low-emitting materials
- High performance backing contains materials from responsible reforestation program
- Carpet and Rug Institute Green Label Plus approved for indoor air quality
- Superior noise reduction rating - 61 IIC, 63 FIC
- Diminishes impact sound
- Smooths concrete and other subfloors
- R-Value 0.64/ASTM C518

Specifications

Green Approved

Green Label Plus approved by CRI (Carpet and Rug Institute) Indoor Air quality Testing Program

Usage

Heavy Residential
Moderate Commercial

Installations

Conventional installation and double glue
Above and Below grade
Over radiant floors

Thickness

3.5 mm (0.138")

Density

352.4 kg/m³ (22 lb / ft³)

Roll size

21 m² (25 yd² 225 ft²) 6 ft wide

Backing

High performance / TEXTRON[®]

Type

100% open cell rubber

Flame Retardant

Passes Pill Test

Member of CCC (Carpet Cushion Council)

Warranty

Guaranteed for the useful life of the original carpet when installed wall to wall

Foam Solutions Inc.
www.foamsolutionsinc.com



MADE  CANADA