

FIBEROCK® Panels

Floor and Wall Applications

Engineered for strength, durability and resistance to moisture and mould, FIBEROCK® brand panels are like nothing else on the market. CGC's patented technology creates a uniform composition that requires no face paper and provides integral water resistance. These versatile panels can be used with a variety of finishes. And, they contain 95 percent recycled material and have earned independent certification from Scientific Certification Systems (SCS) for this achievement.

	 Abuse Resistance	 Fire Resistance	 Water Resistance	 Aesthetics	 Mould Resistance	 Sustainability/ Recycled Content		
		cUL Classification	AQUA-TOUGH™ Formulation	Finishes Like Drywall	Score 10 when tested per ASTM D3273	Post-Industrial	Post-Consumer	
Interior Floors and Walls								
Wet and Dry Areas								
 <p>FIBEROCK® AQUA-TOUGH™ Underlayment</p> <p>This all-purpose substrate is engineered with an unbeatable combination of strength, versatility and water resistance for wet and dry areas throughout the home including kitchens, bathrooms, foyers and laundry rooms. Use under ceramic tile, vinyl tile and vinyl sheet flooring.</p>	Very good	N/A	Yes	N/A	10	85	10	
 <p>FIBEROCK® AQUA-TOUGH™ Tile Backerboard</p> <p>These panels are designed for tile wall and flooring assemblies in areas where resistance to moisture and mould is especially important. Ideal as an upgrade and alternative to green board. Panels can be tiled, painted and wallpapered.</p>	Very good	FRX-G	Yes	Yes	10	85	10	

Product Information

See cgcinc.com for the most up-to-date product information.

Trademarks

The CGC Logo is a trademark of CGC Inc. CGC Inc. is a licensed user of the trademarks AQUA-TOUGH and FIBEROCK.

Note

Products described here may not be available in all geographic markets. Consult your CGC sales office or representative for information.

Notice

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.