

Safety Data Sheet

NA 310 SELF LEVELING PRIMER

Safety Data Sheet dated: 7/5/2018 - version 1

Date of first edition: 7/5/2018

1. Identification

Product identifier

Mixture identification:

Trade name: NA 310 SELF LEVELING PRIMER

Recommended use and restrictions on use

Recommended use: Acrylic polimer solution

Restrictions on use: N.A. **Supplier's details**

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN Phone: 1-450-662-1212

Emergency phone number

(USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-613-996-6666

2. Hazard identification



Classification of the product

Carc. 1A May cause cancer if inhaled.

Aquatic Acute 3 Harmful to aquatic life.

Label elements

Pictograms and Signal Words



Danger

Hazard statements:

H350 May cause cancer if inhaled.
H402 Harmful to aquatic life.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Other hazards

None

Ingredient(s) with unknown acute toxicity

None

3. Composition/information on ingredients

Substances

N.A.

Mixtures

List of components

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 1 of 8

| Quantity | Name | Ident. Numb. | Classification |
|-------------|--------------------|----------------|---|
| 0.25-0.49 % | Ammonium hydroxide | CAS:1336-21-6 | Skin Corr. 1B, H314; Aquatic Acute 1, H400; Acute Tox. 4, H302; Eye Dam. 1, H318; STOT SE 3, H335 |
| 0.1-0.25 % | Ethylene glycol | CAS:107-21-1 | Acute Tox. 4, H302; STOT RE 2, H373; Eye Irrit. 2B, H320; STOT SE 2, H371 |
| 0.1-0.25 % | Talc | CAS:14807-96-6 | Carc. 1A, H350 |

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

N.A.

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

5. Fire-fighting measures

Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

 $Burning\ produces\ heavy\ smoke.$

Hazardous combustion products: N.A. Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 2 of 8

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Storage temperature: N.A. Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8. Exposure controls/personal protection Control parameters

List of components with OEL value

| Component | OEL Type Country | Ceiling | Long Term mg/m3 | Long Term ppm | Short Term mg/m3 | Short Term ppm | Behaviour | Note |
|-----------------|------------------|---------|--------------------|------------------|---------------------|----------------|------------|---|
| Ethylene glycol | ACGIH | С | | | 100 | | | |
| | EU | | 52 | 20 | 104 | 40 | Indicative | Possibility of significant uptake through the skin; |
| Talc | ACGIH | | 2 | | | | | A4 - Not Classifiable as a Human Carcinogen (containing no asbestos fibers);pulmonary fibrosis (containing no asbestos fibers);pulmonary function (containing no asbestos fibers); |

Appropriate engineering controls

N.A.

Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: light violet

Odour: like: Acrylate
Odour threshold: N.A.

pH: 7.50

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 100 °C (212 °F)

Flash point: >100 °C (212 °F)

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.03 g/cm3
Solubility in water: Miscible
Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.A.

Explosive properties: N.A.
Oxidizing properties: N.A.
Solid/gas flammability: N.A.

Other information

Substance groups relevant properties: N.A.

Miscibility: N.A. Fat Solubility: N.A.

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 3 of 8

Conductivity: N.A.

10. Stability and reactivity

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects

Toxicological information of the mixture:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

Ammonium hydroxide

a) acute toxicity

LD50 Oral Rat = 350 mg/kg

Ethylene glycol

a) acute toxicity

LD50 Oral Rat = 4000 mg/kg

LD50 Skin Rat = 10600 mg/kg

If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

Substance(s) listed on the IARC Monographs:

Talc Group 3

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. Ecological information

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

List of components with eco-toxicological properties

| Quantity | Component | Ident. Numb. | Ecotox Infos |
|----------------|--------------------|----------------|--|
| 0.25-0.49 % | Ammonium hydroxide | CAS: 1336-21-6 | a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 82 mg/L 96h |
| | | | a) Aquatic acute toxicity: EC50 Daphnia water flea = 66 mg/L 48h |
| | | | a) Aquatic acute toxicity: EC50 Daphnia Daphnia pulex = 66 mg/L 48h |

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 4 of 8

CAS: 107-21-1

a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss = 41000 mg/L 96h IUCLID

a) Aquatic acute toxicity: LC50 Fish Oncorhynchus mykiss 14 mL/L 96h EPA

a) Aquatic acute toxicity: LC50 Fish Lepomis macrochirus = 27540 mg/L 96h EPA

a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 40000 mg/L 96h EPA

a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata = 16000 mg/L 96h IUCLID

a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio > 100 g/l 96h

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 46300 mg/L 48h IUCLID

a) Aquatic acute toxicity: EC50 Algae Pseudokirchneriella subcapitata 6500 mg/L 96h IUCLID

0.1-0.25 % Talc CAS: 14807-96-6

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. Disposal considerations

Safe handling and methods for disposal

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. Transport information

UN number

TDG-UN number: N/A ADR-UN number: N/A DOT-UN Number: N/A IATA-Un number: N/A IMDG-Un number: N/A

UN proper shipping name

TDG-Shipping Name: N/A
ADR-Shipping Name: N/A
DOT-Proper Shipping Name: N/A
IATA-Technical name: N/A
IMDG-Technical name: N/A

Transport hazard class(es)

TDG-Class: N/A
ADR-Class: N/A
DOT-Hazard Class: N/A
IATA-Class: N/A
IMDG-Class: N/A

Packing group

TDG-Packing Group: N/A
ADR-Packing Group: N/A
DOT Packing Group: N/A
IATA-Packing group: N/A
IMDG-Packing group: N/A

Environmental hazards

Marine pollutant: No

Environmental Pollutant: N.A.

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

Special precautions in connection with transport or conveyance

TDG:

TDG Special provisions: N/A
Department of Transportation (DOT):
DOT-Special Provision(s): N/A

DOT-Label(s): N/A DOT-Symbol: N/A

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 5 of 8

DOT-Cargo Aircraft: N/A DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A DOT-Non-Bulk: N/A Road and Rail (ADR-RID):

ADR-Label: N/A

ADR-Hazard identification number: N/A

ADR-Transport category (Tunnel restriction code): N/A

Air (IATA):

IATA-Passenger Aircraft: N/A IATA-Cargo Aircraft: N/A

IATA-Label: N/A IATA-Subrisk: N/A IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A
IMDG-Stowage Note: N/A
IMDG-Subrisk: N/A

IMDG-Special Provisions: N/A

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: N/A IMDG-MFAG: N/A

15. Regulatory information

Canada - Federal regulations

DSL - Domestic Substances List

DSL Inventory:

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL Inventory:

no substances listed

NPRI - National Pollutant Release Inventory

Substances listed in NPRI:

no substances listed

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Ammonium hydroxide is listed in TSCA Section 8b

Ethylene glycol is listed in TSCA Section 8b Section 5

Talc is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

no substances listed

Section 304 - Hazardous substances:

Ammonium hydroxide

Ethylene glycol

Section 313 - Toxic chemical list:

Ethylene glycol

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

Ammonium hydroxide Reportable quantity: 1000 pounds
Ethylene glycol Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 6 of 8

Ethylene glycol is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

Ammonium hydroxide is listed in CWA Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

Ethylene glycol Listed as reproductive toxicant

Talc Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

Ammonium hydroxide
Ethylene glycol

Talc

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Ammonium hydroxide
Ethylene glycol

Talc

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

Ammonium hydroxide
Ethylene glycol

Talc

16. Other information

| Code | Description |
|------|---|
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H320 | Causes eye irritation. |
| H335 | May cause respiratory irritation. |
| H350 | May cause cancer. |
| H350 | May cause cancer if inhaled. |
| H371 | May cause damage to organs . |
| H373 | May cause damage to organs through prolonged or repeated exposure . |
| H400 | Very toxic to aquatic life. |
| H402 | Harmful to aquatic life. |
| | |

Safety Data Sheet dated: 7/5/2018 - version 1

Product code: 9074938

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 7 of 8

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Date 7/5/2018 Production Name NA 310 SELF LEVELING PRIMER Page n. 8 of 8