*** CARPET TILE 7805 AEROSPACE COORDINATES WITH 7806 SKYLINE

















SPECIFICATIONS

Supplier: Kraus[®]

Fiber System: 100% BCF Solution Dyed Nylon **Modular Size:** 23.6" × 23.6" 60 cm × 60 cm

Backing System: EuroBac™

Construction: Multi-Level Loop

39.4 rows/10 cm Gauge: 1/10 42.9 stitches/10 cm Stitches: 11 s.p.i. 4303 8.7 kilotex/cm² **Density:** Pile Height: 0.10"/0.24" 2.5 mm/6 mm Pile Weight: $20 \text{ oz.}/\text{v}^2$ 680 a/m2 Static generation: 3.0 kV or less (AATCC 134)

Flammability: ASTM E648 - Class I (direct glue)

DOC FF 1-70 - passes

Colorfastness to light: 5.0 (AATCC 16)
CRI/CCI air quality test: Green Label Plus

Environmental: Eligible for any recycling program

Recycled Content: EuroBac™ Modular backing

- min. 20% pre-consumer











CARTON CONFIGURATION

Pcs/Carton: 14 | 39 lbs/carton

Packaging: 6.03 sq.yd./carton | 40 cartons/pallet Installation: Kraus | Premium Adhesive™ KPA-31

WARRANTIES

Lifetime Commercial Wear **Lifetime** Backing Performance

INSTALLATION METHODS









FFATURES

Wear Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.

Backing Performance Kraus carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. Product image colors may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus Premium Adhesive is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See harrisflooring.com for latest specifications.