

Shown: 28522 12x24 Almond Note, 28522/M1x6 Almond Note Bar Mosaic

RHYME

в y floridatile

Typical Uses

Rhyme color body porcelain floor and wall tile is appropriate for all residential and commercial wall, countertop and backsplash applications, all residential and most commercial floor applications.

Notice: Not all flooring products are suitable for wet areas, specialized applications or commercial use. Please refer to the American National Standard Specifications for Ceramic Tile (ANSI A137.1) for ceramic, stone and glass installation for specific usage and installation information.

This Florida Tile product will contribute to USGBC LEED points and the ANSI approved NAHB Green Building Points.

Field Tile Nominal Size ¹	Metric (cm)	Pcs./Sq Ft ²	Thickness ³
12" x 24"	30 x 60	.5	9mm

¹These values may vary from lot to lot.

³ May not apply to textured surfaces or tiles with uneven back patterns.

Trim	Shape	SKU	Nominal Size	Metric (cm)	
Bullnose		P43C9	3" x 12"	7.5 x 30	_

Properties (Floor)	ASTM	ANSI	Results ¹
DCOF AcuTest ²	A137.1	≥0.42	Pass
Visible Abrasion Resistance	C-1027	As reported ³	Class III
Glaze Hardness	Mohs Scale	N/A	7 Mohs
Break Strength	C-648	250 lbs.	Pass
Water Absorption	C-373	≤0.5%	≤0.5%

¹These tests are performed by a 3rd party testing lab using industry standard equipment and techniques. Values are offered in good faith as being accurate and typical of normal production. Due to the natural variation of raw materials and manufacturing processes, the values of the purchased product for any

Color Variations

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.



V1 = Uniform Appearance

Differences among pieces from the same productions run are minimal.















²These values are based on actual sizes including the grout joint.

particular installation may vary.

ANSI A137.1 standard, ceramic tiles selected for level interior spaces expected to be walked upon when wet must have a minimum wet DCOF AcuTest value of 0.42.

 $^{^3}$ Class 0 Not recommended for floors, Class I Light Residential, Class II Residential, Class III Heavy Residential or Light Commercial, Class IV Commercial, Class V Heavy Commercial.