



# TECHNICAL DATA SHEET

## *Grout Finish*

### Penetrating Grout Colourant

#### Description

R&D Grout Finish is a water-based polymer modified penetrating grout stain and sealer which re-colours and rejuvenates grout. R&D Grout Finish forms a protective barrier against organic food stains, grease, soil and other forms of foreign deposit.

#### Typical Uses

- Designed for use on cement-based grouts, epoxy grouts and urethane grouts on showers, countertops, backsplashes, floors and walls

#### Limitations

- Always test a small area to ensure suitability
- Surfaces are usable 24 hours after application for most uses
- Full cure time is approximately 36-48 hours
- Apply only in temperatures between 10-25°C (50-80°F)
- Not suitable for submerged areas
- Keep from freezing
- Store between 10-32°C (50-90°F)

#### Application

- Shake well before using
- Read all instructions thoroughly before applying
- Surface must be clean, dry and free of any sealers, repellants, efflorescence, dirt, oil, wax or grease

- Apply using roller or brush applicator in one direction along vertical grout joints, then in one direction along horizontal grout joints
- Wipe excess stain off tile surface while still wet with a slight damp sponge
- Do not allow to dry on tile face
- Allow to dry thoroughly
- A second coat may be applied 60-90 minutes later, after first coat has dried
- Protect from traffic for a minimum of 2 hours
- Protect from water for at least 24 hours

#### Theoretical Coverage

- Approximately 5-28 m<sup>2</sup> (50-300 sq.ft.) per 236ml (8oz.) bottle depending on width of grout joint and size of tile

#### Safety Precautions

Please refer to product Safety Data sheet.