

Making Dream Surfaces Attainable

Brickstone Porcelain Collection


www.msisurfaces.com

Colors



Ivory 2"x10"

Red 2"x10"





Cobble 2"x10"





Taupe 2"x10"



White Brick 2"x10"



Putty 2"x10"

Size	Size Thic		ness IVORY			RED		TAUPE		WHITE BRICK		
2-1/3X10 3/		3/8"		NCAPIVOBRI2X1		NCAPREDBRI2X10		NCAPTA	NCAPTAUBRI2X10		NCAPWHIBRI2X10	
5x10 3/		3/8"		NCAPIVOBRI5X1		NCAPREDBRI5X10		NCAPTAUBRI5X10				
Size Thick		nickness	s FOG			COBBLE		PUTTY		CHARCOAL		
2-1/3X10		3/8"		NCAPFOGBRI2X10		NCAPCOBBRI2X10		NCAPPU	TBRI2X10	NCAPCHABRI2X10		
APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variat	ion	COF	Breaking Strength		Water Absorption	Hardness	
RESIDENTIAL	۲	۲	۲									
LIGHT COMMERCIAL	۲	۲	۲	IV	V4	1	DCOF - > 0.42 W	et > 2	75 lbf	< 0.5%	7	
HEAVY COMMERCIAL			۲									
Freeze / Th	C	Chemical Resistance				Rectified/ Non-Rectified			Glazed / Non Glazed			
Resistan		Resistant				Pressed			Glazed			

The new "brick" tiles will add to the existing cotto and wood planks of this great looking, trend forward series, Capella. The brick tiles can be featured as a back splash or to compliment the cotto or wood planks for both floor and wall applications. Available in two realistic brick sizes 2¹/₃"x10" and 5"x10".

Technical Information

Primary Colors: Beige, Ivory, Red, White Material Type: Glazed Porcelain Finish: Matte

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Features At A Glance

- Real brick looks created with porcelain
- Classic $2^{1/3} \times 10$ in four colors and 5×10 sizing in 3 different colors
- Ink Jet technology with 3D punch for realistic brick looks

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer: Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile. To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns. *No claims accepted after tile installation.