



Osmo Liquid Wax Cleaner Application Instructions

Cleaning & Removing Stains

Apply a small amount on a cloth or White Scotchbrite pad and scrub the dirty area

1. First clean the wood surface with Osmo Wash & Care and wipe dry
2. Using a White Scotchbrite pad, scrub a small amount of the product into the dirty area
3. Wipe away dirt residues

For Heavier Stains: Apply to floor with Osmo polishing pad (very thin steel wool) or on Oak floors, a Green Scotchbrite pad. Wipe off dirt residues and reapply Osmo Polyx®-Oil to area and blend into the existing finish.

Refreshing Manually with Osmo Opti-Set

Apply a thin coat with the Active Fibre Cloth included in the Osmo Opti-Set

1. First clean the wood surface with Osmo Wash & Care and wipe dry
2. Using the Active Fibre Cloth work a thin and even coat of the Liquid Wax Cleaner across the floor.
3. Approx. 1 hour drying time. Allow for good ventilation whilst drying

4. Can be polished to raise sheen, once dried with a clean micro-fibre cloth

Mechanically with a Floor Buffer

Apply a thin coat with an Osmo FloorxCenter and MicroPad; or other single disc buffer and carpet

1. First clean the wood surface with Osmo Wash & Care and wipe dry
2. Using the MicroPad, work a thin and even coat of the Liquid Wax Cleaner across the floor.
3. Approx. 1 hour drying time. Allow for good ventilation whilst drying
4. Can be polished to raise sheen, once dried

Manually with a Cloth/Rag

Apply a thin coat with a clean lint-free cloth, or microfiber cloth

1. First clean the wood surface and wipe dry
2. Using the cloth work a thin and even coat of the Liquid Wax Cleaner into the wood
3. Approx. 1 hour drying time. Allow for good ventilation whilst drying
4. For Furniture, additional coats may be added to further protect
5. Can be polished to raise sheen, once dried, with a clean lint-free cloth