

# Single-Phase Dust Extractors

## DC 2900c



The DC 2900c is our most popular dust extractor. It is suitable for vacuum cleaning and source extraction from handheld power tools (with suction casings up to Ø 125mm/5") and small table saws. The DC 2900c has a sturdy steel chassis with large wheels, but is still light and portable.

### Part No DC 2900c, 50/60 Hz

120000	230V /50 Hz, EU
120003	230V /50 Hz, UK
120008	230V /50 Hz, CH
120013	115V /50 Hz, UK
120015	115V /60 Hz, US/CAN
120100	230V /50 Hz, Auto start*, EU
120103	230V /50 Hz, Auto start, UK*

\*) DC 2900 Autostart. Plug the handheld power tool into the power socket on the unit. Set the selector switch to the AUTO position. The dust extractor will start automatically when the power tool is started.



### Supplied with (Part No)

Suction hose (Ø38mm/1.5"), 5 m/16 ft (2111)  
 Antistatic suction hose (Ø38/1.5"), 5 m/16 ft (2012)  
 UK/US/CAN models  
 Connecting sleeve (2115)  
 Coupling socket (2108)  
 Floor nozzle B370 /W17" (7235)  
 Chrome suction pipe Ø38mm/1.5" (7257)  
 Plastic bag (42702)  
 Fine filter, cellulose (42029)  
 HEPA H13 filter (42027)

### Technical data

H x W x L (cm/inch)	111x44x55 /43"x17"x21"
Weight	14 kg /30.8 lbs
Hose length	5 m /16 ft Ø38 mm /1.5"
Collector	20 l /5.3 US gal
Flow at open inlet	190 m³/h /114 cfm
Negative pressure, max 115/230V	21/24 kPa /84/96 inwg
Power consumption 115/230V	1285/1340 W
Sound level	68 dB(A)

## DC 2900a

Collection in a container makes the DC 2900a ideal to use for sharp material such as metal chips.

### Part No DC 2900a, 50/60 Hz

121000	230V /50 Hz, EU
121003	230V /50 Hz, UK
121008	230V /50 Hz, CH
121013	115V /50 Hz, UK
121015	115V /60 Hz, US/CAN
121100	230V /50 Hz, Auto start*, EU

### 121000-3 DC 2800H ENT 230V/50Hz

Based on the DC 2900a. The machine has a switch allowing the user to choose the level of air flow at which a warning signal shall be given.



### Supplied with (Part No)

Suction hose (Ø38 mm/1.5"), 5 m/16 ft, antistatic (2012)  
 Floor nozzle B370 /W17" (7235)  
 Chrome suction pipe Ø38 mm/1.5" (7257)  
 Fine filter, polyester (42028)  
 HEPA H13 filter (42027)

### Technical data

H x W x L (cm/inch)	111x44x55/ 43"x17"x21"
Weight	19 kg /42 lbs
Hose length	5 m /16 ft Ø38 mm /1.5"
Container	40 l /10.56 US gal
Flow at open inlet	190 m³/h /114 cfm
Negative pressure, max 115/230V	21/24 kPa /84/96 inwg
Power consumption 115/230V	1285/1340 W
Sound level	68 dB(A)