## **Safety Data Sheet CHEMBOND LFT PRO 8870 GRAY**

Safety Data Sheet dated: 07/28/2023 - version 1

Date of first edition: 07/28/2023



### 1. Identification

#### **Product identifier**

Mixture identification:

Trade name: CHEMBOND LFT PRO 8870 GRAY

Trade code: 9029011

Recommended use and restrictions on use

Recommended use: Polymer modified mortar

Restrictions on use: Not available

Supplier's details

Company: MAPEI INC. (Canada)

2900 Francis-Hughes Avenue H7L 3J5 - Laval - QC - CAN

Phone: 1-450-662-1212

Responsible: RDProductSafety@mapei.com

**Emergency phone number** 

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

### 2. Hazard identification







# Classification of the product

Skin corrosion, Category 1A Causes severe skin burns and eye damage.

Serious eye damage, Category 1 Causes serious eye damage.

Skin Sensitization, Category 1 May cause an allergic skin reaction.

Carcinogenicity, Category 1A May cause cancer if inhaled. Specific target organ toxicity following single exposure, May cause respiratory irritation.

Category 3

Specific target organ toxicity following repeated exposure,

Category 1

Causes damage to organs through prolonged or repeated exposure if inhaled.

# **Label elements**

## Hazard pictograms and Signal Word



### **Hazard statements**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350 May cause cancer if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

#### **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n. 1 of 9

| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
|----------------|--|
| P301+P330+P331 | IF SWALLOWED: rinse mouth. Do NOT induce vomiting.   |
| P302+P352      | IF ON SKIN: Wash with plenty of water.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.                             |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P310           | Immediately call a doctor.   |
| P321           | Specific treatment (see supplementary instructions on this label)  |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with applicable regulations.   |

## Other hazards

None

## Ingredient(s) with unknown acute toxicity

None

## 3. Composition/information on ingredients

#### **Substances**

Not Relevant

#### **Mixtures**

Hazardous components within the meaning of WHMIS 2015 and related classification:

### List of components

| Qty     | Name   | Ident. Numb.                   | Classification   | Registration Number |
|---------|--|--------------------------------|--|---------------------|
| 50-75 % | silica sand; quartz                          | CAS:14808-60-7<br>EC:238-878-4 | ' STOT RE 1, H372; Carc. 1A, H350  |                     |
| 25-50 % | portland cement; cement, portland, chemicals |                                | STOT SE 3, H335; Eye Dam. 1,<br>H318; Skin Sens. 1, H317; Skin<br>Corr. 1A, H314 |                     |
| 1-2.5 % | calcium diformate                            | CAS:544-17-2<br>EC:208-863-7   | Eye Dam. 1, H318; Comb. Dust, CANH003  |                     |

The actual concentration of the components listed above is withheld as a trade secret.

#### 4. First-aid measures

# Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

 $\label{lem:lemove} Remove\ contaminated\ clothing\ immediately\ and\ dispose\ of\ safely.$ 

After contact with skin, wash immediately with soap and plenty of water.

If skin irritation or rash occurs: Get medical advice/attention.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n. 2 of 9

### Most important symptoms/effects, acute and delayed

Eve irritation

Eye damages

Skin Irritation

Ervthema

#### Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

#### 5. Fire-fighting measures

## Suitable and unsuitable extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

### Specific hazards arising from the hazardous product

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant Oxidizing properties: Not Relevant

### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

## Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

# 7. Handling and storage

## Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Do not breathe dust.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Wash skin thoroughly after handling.

See also section 8 for recommended protective equipment.

### Conditions for safe storage, including any incompatibilities

Store cool and dry.

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n.

3 of 9

# 8. Exposure controls/personal protection

## **Control parameters**

### **Community Occupational Exposure Limits (OEL)**

|  | OEL<br>Type | Country         | Occupational Exposure Limit  |
|--|-------------|-----------------|--|
| silica sand; quartz<br>CAS: 14808-60-7                             | ACGIH       |                 | Long Term: 0.025 mg/m3<br>A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;  |
|  | ACGIH       |                 | Long Term: 0.025 mg/m3<br>A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis   |
|  | MAK         | AUSTRIA         | Long Term: 0.15 mg/m3  |
|  | MAK         | SWITZERLAN<br>D | Long Term: 0.15 mg/m3  |
| portland cement; cement,<br>portland, chemicals<br>CAS: 65997-15-1 | OSHA        |                 | Long Term: 15 mg/m3  |
|  | OSHA        |                 | Long Term: 5 mg/m3   |
|  | ACGIH       |                 | $  \mbox{Long Term: 1 mg/m3} \\ \mbox{A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;} $ |
|  | ACGIH       |                 | Long Term: 1 mg/m3<br>A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory<br>symptoms;asthma                  |
|  | MAK         | AUSTRIA         | Long Term: 5 mg/m3   |
|  | MAK         | SWITZERLAN<br>D | Long Term: 5 mg/m3   |

#### **Appropriate engineering controls**

Not available

## Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min. Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to  $29 \ \text{CFR} \ 1910.134 - \text{CSA} \ \text{Z94.4}$  for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

# 9. Physical and chemical properties

# Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: powder Grey

Odour: cement like

Odour threshold: Not Relevant

pH: Not Relevant

pH (water dispersion, 10%): 12.00

Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant

Flash point: Not Relevant Evaporation rate: Not Relevant

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n. 4 of 9

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant Vapour pressure: Not Relevant Relative density: 2.15 g/cm3 Solubility in water: dispersible Solubility in oil: Not Relevant

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant Decomposition temperature: Not Relevant

Viscosity: Not Relevant

Explosive properties: Not Relevant Oxidizing properties: Not Relevant Solid/gas flammability: Not Relevant

#### Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant Fat Solubility: Not Relevant Conductivity: Not Relevant

### 10. Stability and reactivity

## Reactivity

Stable

#### Chemical stability

Data not available.

#### Possibility of hazardous reactions

None.

#### **Conditions to avoid**

No data available

#### **Incompatible materials**

Data not available.

#### **Hazardous decomposition products**

Data not available.

### 11. Toxicological information

f) carcinogenicity

### Information on toxicological effects

Likely routes of exposure:

Skin contact, skin absorption, eye contact, inhalation and ingestion.

### **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met
b) skin corrosion/irritation The product is classified: Skin corrosion, Category 1A(H314)
c) serious eye damage/irritation The product is classified: Serious eye damage, Category 1(H318)
d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure The product is classified: Specific target organ toxicity following single exposure,

Category 3(H335)

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure,

Category 1(H372)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

## Toxicological information on main components of the mixture:

silica sand; quartz a) acute toxicity LD50 Oral Rat = 500 mg/kg

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n. 5 of 9

a) acute toxicity LD50 Oral Rat = 2650 mg/kg

## Substance(s) listed on the IARC Monographs:

silica sand; quartz Group 1

### Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

### Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

### Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

### 12. Ecological information

#### **Ecotoxicity**

calcium diformate

Adopt good working practices, so that the product is not released into the environment.

### List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

#### List of Eco-Toxicological properties of the components

Component Ident. Numb. **Ecotox Data** 

silica sand; quartz CAS: 14808-60- a) Aquatic acute toxicity : LC50 carp > 10000 mg/L 72h

7 - EINECS: 238-878-4

CAS: 544-17-2 - a) Aquatic acute toxicity: LC50 Fish Brachydanio rerio >= 1000 mg/L 96h calcium diformate

EINECS: 208-TUCL ID

863-7

### Persistence and degradability

NΑ

## **Bioaccumulative potential**

### Mobility in soil

NΑ

## Other adverse effects

N.A.

### 13. Disposal considerations

#### Safe handling and methods for disposal

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

## Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

## Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

### 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

#### **UN** number

TDG-UN number: Not Applicable ADR-UN number: Not Applicable DOT-UN Number: Not Applicable IATA-Un number: Not Applicable IMDG-Un number: Not Applicable

### UN proper shipping name

TDG-Shipping Name: Not Applicable
ADR-Shipping Name: Not Applicable
DOT-Proper Shipping Name: Not Applicable
IATA-Technical name: Not Applicable
IMDG-Technical name: Not Applicable

## Transport hazard class(es)

TDG-Class: Not Applicable
ADR-Class: Not Applicable
DOT-Hazard Class: Not Applicable
IATA-Class: Not Applicable
IMDG-Class: Not Applicable

## **Packing group**

TDG-Packing Group: Not Applicable ADR-Packing Group: Not Applicable DOT Packing Group: Not Applicable IATA-Packing group: Not Applicable IMDG-Packing group: Not Applicable

#### **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

### Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Not Applicable

## Special precautions in connection with transport or conveyance

TDG:

Not Applicable

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

## 15. Regulatory information

## Canada - Federal regulations

**DSL - Domestic Substances List** 

All the substances are listed in the DSL.

**NDSL - Non Domestic Substances List** 

This product complies with NDSL inventory

**NPRI - National Pollutant Release Inventory** 

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

#### **USA** - Federal regulations

#### **TSCA - Toxic Substances Control Act**

All the components are listed on the TSCA inventory

## **TSCA listed substances:**

silica sand; quartz is listed in TSCA Section 8b portland cement; cement, is listed in TSCA Section 8b

portland, chemicals

calcium diformate is listed in TSCA Section 8b

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n. 7 of 9

### **SARA - Superfund Amendments and Reauthorization Act**

#### **Section 302 - Extremely Hazardous Substances:**

No substances listed

#### Section 304 - Hazardous substances:

No substances listed

#### Section 313 - Toxic chemical list:

No substances listed

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

## Substance(s) listed under CERCLA:

No substances listed

#### CAA - Clean Air Act

#### **CAA listed substances:**

No substances listed

### **CWA - Clean Water Act**

#### **CWA listed substances:**

No substances listed

#### **USA - State specific regulations**

### **California Proposition 65**

#### Substance(s) listed under California Proposition 65:

silica sand; quartz

Listed as carcinogen

### Massachusetts Right to know

### Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

#### Pennsylvania Right to know

## Substance(s) listed under Pennsylvania Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

## New Jersey Right to know

### Substance(s) listed under New Jersey Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

## 16. Other information

Codo

Safety Data Sheet dated: 7/28/2023 - version 1

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Doccrintion

| Code    | Description                                |                                |
|---------|--|--------------------------------|
| CANH003 | May form combustible dust concentrations i | n air.                         |
| H314    | Causes severe skin burns and eye damage.   |                                |
| H317    | May cause an allergic skin reaction.       |                                |
| H318    | Causes serious eye damage.                 |                                |
| H335    | May cause respiratory irritation.          |                                |
| H350    | May cause cancer.                          |                                |
| H372    | Causes damage to organs through prolonge   | d or repeated exposure.        |
| Code    | Hazard class and hazard category           | Description                    |
| A.2/1A  | Skin Corr. 1A                              | Skin corrosion, Category 1A    |
| A.3/1   | Eye Dam. 1                                 | Serious eye damage, Category 1 |
| A.4.2/1 | Skin Sens. 1                               | Skin Sensitization, Category 1 |

A.6/1A Carc. 1A Carcinogenicity, Category 1A

A.8/3 STOT SE 3 Specific target organ toxicity following single exposure, Category 3
A.9/1 STOT RE 1 Specific target organ toxicity following repeated exposure, Category 1

CAN-ADD/CD Comb. Dust Combustible Dusts — Category 1

### Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Print date 08/04/2023 Production Name CHEMBOND LFT PRO 8870 GRAY Page n. 9 of 9