

GatorLOC

Lock Down High Quality in
Minutes. GatorLOC.

**SEAMLESS
INTERLOCK**

**VIRTUALLY
ODOURLESS**

**COMMERICAL
GRADE**

Turn any area into a functional fitness space in just minutes with GatorLOC interlocking loose-laying tiles. With no adhesive required, the easy to install GatorLOC tiles are ideal for even the most novice DIYer.

Precision cut to form a tight interlock, your finished flooring will have virtually invisible seams, and leave you looking like a pro in no time. Minimal maintenance GatorLOC is regarded as the premier choice of professionals and DIYer like.



STANDARD TILE SPECIFICATIONS

SIZE	THICKNESS	BINDER
2'0" x 2'0"	5/16" (8MM)	URETHANE

* CUSTOM THICKNESSES AVAILABLE



COLOURED EPDM GRANULATE

1MM TO 3MM

* THE COLOUR CONCENTRATION OF THE STANDARD TILE IS 30%

GATORLOC SPECIFICATIONS

TEST TYPE	ASTM	RESULTS
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95%*-120%*
TENSILE STRENGTH	D-412	260-340 PSI
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	<0.5MG/M ²
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE-C TEAR	D-624	80 MIN
SURFACES FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*


* VARIES BASED ON COLOUR

NOTE: PHYSICAL PROPERTIES CAN VARY BY PRODUCT TYPE.

INFORMATION ABOVE APPLIES TO THIS PRODUCT ONLY.




0200 Midnight Black



0201 Cobalt Frost



0202 Sandstone



0203 Steel Frost



0204 Sable Black

* Additional colours available for custom orders