



GatorPRO

7 Million Reps Can't Be Wrong.
Are You Ready to Roll?

**HIGH
PERFORMANCE**

**MAXIMUM
DURABILITY**

**COMMERCIAL
GRADE**

Economical GatorPRO rolls are excellent for use in high-wear, high-impact spaces that require maximum protection and durability. Manufactured from post-consumer recycled rubber, rolls are available in a variety of colours and thicknesses.

GatorPRO rolls provide superior slip-resistance in wet or dry conditions; while combining anti-fatigue and ergonomic comfort properties with low maintenance to produce the ultimate flooring solution for a variety of applications.



2007 - 4 Highland Park Green NE
Airdrie, AB T4A 0X3

587.775.8838
888.363.6289

sales@perfectsurfaces.ca

www.perfectsurfaces.com





WIDELY REGARDED AS THE PREMIER "GREEN"
RESILIENT FLOORING CHOICE, GATORPRO
CONTAINS UP TO 92% RECYCLED CONTENT
AND LOW VOC EMISSIONS

STANDARD ROLL SPECIFICATIONS

WIDTH*	LENGTH*	WIDTH TOLERANCES	BINDER
4'0"	25'0"	48" CUT @ 48.5" +/- .24"	URETHANE

* CUSTOM ROLL SIZES AVAILABLE

THICKNESS

1/8" (3MM), 1/4" (6.5MM), 5/16" (8MM), 3/8" (9.5MM), 1/2" (12.5MM)

COLOURED EPDM GRANULATE

1MM TO 3MM

* COLOUR CONCENTRATION OF A STANDARD ROLL IS 10%



GATORPRO SPECIFICATIONS


TEST TYPE	ASTM	RESULTS
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95%*-120%*
TENSILE STRENGTH	D-412	260-340 PSI
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	<0.5MG/M ²
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE-C TEAR	D-624	80 MIN
SURFACES FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*

* VARIES BASED ON COLOUR


NOTE: PHYSICAL PROPERTIES CAN VARY BY PRODUCT TYPE.
INFORMATION ABOVE APPLIES TO THIS PRODUCT ONLY.



0101 Pitch Black




0103 Arctic Blue




0104 Sandstorm




0106 Fog White



0107 Fire Red



0109 Anytime Purple



0110 Teal Green

* Additional
colours available
for custom orders