

Symbio TSYM

Carpet Tiles • Mainstreet Tiles - Nyluxe

Benefits

Safe and healthy

Green Label Plus certified ensuring that you are purchasing the very lowest VOC-emitting products on the market
Improves indoor air quality by trapping particles, removing them from the breathing zone and reducing their circulation
Slip Resistant
Soft to the touch but also for the body thanks to its shock absorption capacity which helps limit damage to muscles and articulations

Environmentally-Friendly

Made with solution-dyed fibers a process that reduces significantly water consumption

Best-in-class Warranty

30 Days No Questions Asked Replacement

Limitless designabilities

One of the most versatile floor coverings because you get to choose from a wide range of colors and textures
Easy to mix and match colors and designs for a personalized look

Warm, quiet and comfortable

Without a doubt, the most comfortable flooring
Greatest soundproofing and insulating properties
Reduces heat loss
Soft and warm to the touch

Quickship

Stock product for faster delivery

Stain resistant & easy to clean

Protected with Stain Control for resistance to the most stubborn stains
Treated with SoilScreen to keep soil on the surface making your carpet easier to clean

High performance

Made with our Nyluxe solution-dyed nylon fiber for outstanding wear resistance
Part of our Mainstreet Nyluxe product offering, ideal for general commercial applications

Easy to install and repair

Easy installation with our 301 Carpet Tiles Adhesive
Modular floor covering for fast and easy repair when needed

Symbio TSYM

Carpet Tiles • Mainstreet Tiles - Nyluxe

Sustainability

Next Generation Sustainable Backing

Eco3RBac isn't just a catchy name, it reflects our dedication to innovation and sustainability. Made entirely from recycled plastic bottles, this new backing challenges common misconceptions about recycled plastics in consumer goods.

Free from PVC, plasticizers, DOP, DINP, bitumen and odors.

Eco3RBac is **made of 100% recycled plastic bottles (PET)**.

20-25% lighter than PVC backing products which means lower energy use during transport and reduced building load.

Provides dimensional stability.

May contribute to obtaining LEED® v4, WELL Building Standard, and Living Building Challenge certifications.

Reduced foot fatigue.

Sound absorption and matches other materials in the room to improve indoor acoustic environment.


Comfort enhancement

Low VOC emission materials

Odor free

Reduced foot fatigue

Sound absorption and matches other materials in the room to improve indoor acoustic environment.



Sustainable certifications



Green Label Plus

S-P-00123 EPD®
environdec.com



Environmental Product
Declaration (EPD)

Symbio TSYM

Carpet Tiles • Mainstreet Tiles - Nyluxe

Product Specifications

Market Segments	Builder, Hospitality, Pro, Property Management, Residential, Senior Living, Workspace
Brand	Nyluxe Tiles
Collection	Mainstreet Tiles - Nyluxe
Style Name	Symbio
Style Number	TSYM
Colors	6
Construction	Multi-Level Loop
Format	Tile
Fiber Type	100% Solution Dyed Nylon
Abrasion Resistance	General Commercial Use
Dye Method	Solution Dyed
Pile Weight	16.02 oz./y ² (543.0 g/m ²)
Pile Height	9/64 in (3.5 mm)
Total Height	17/64 in (6.5 mm)
Backing	Eco3Rbac
Stitch Count	12/in (47/10 cm)
Gauge	1/10 in (2.54 mm)
Density Factor	5852
Static Control	Less Than 2.0 kV (AATCC 134)
Flammability	Meets DOC FF-1-70
Flooring Radiant Panel	Class 1 (ASTM E-648)
Tarr	0
Indoor Air Quality	GLP 101162
Dimension	19.7 x 19.7" (50 X 50 cm)
Color Fastness	Meets 5.0 AATCC 16
Certifications	Green Label Plus, QuickShip, Environmental Product Declaration (EPD), SoilScreen, Stain Control Quarter Turn, Monolithic, Brick
Installation Methods	🔗 Carpet Tiles Installation Guide



Color Names & Numbers

#01	Heavy Steel	#02	Mixed Pebbles
#03	Wild Storm	#04	Noble Owl
#05	Smoky Green	#06	Dried Oregano

Warranties

- [🔗 Carpet Tiles Warranty Guide](#)
- [🔗 Carpet Tiles Care & Maintenance Guide](#)

Residential use	Colorfastness <i>Lifetime</i> No Questions Asked Replacement <i>30 days</i> Delamination Resistance <i>Lifetime</i> Edge Ravelling <i>Lifetime</i> Wear Resistance <i>Lifetime</i> Static Control <i>Lifetime</i> Stain Resistance <i>Lifetime</i> Anti-Zippering <i>Lifetime</i>
Commercial use	Stain Resistance <i>15 Years</i> Colorfastness <i>15 Years</i> Anti-Zippering <i>15 Years</i> Delamination Resistance <i>15 Years</i> Edge Ravelling <i>15 Years</i> Wear Resistance <i>15 Years</i> Static Control <i>15 Years</i>

Symbio TSYM

Carpet Tiles • Mainstreet Tiles - Nyluxe

Colors



#01
Heavy Steel



#02
Mixed Pebbles



#03
Wild Storm



#04
Noble Owl



#05
Smoky Green



#06
Dried Oregano

Packaging information

Units Per Box	20
Boxes Per Pallet	32
Box Weight	30.44 pounds (13806.52 grams)
Square Yards Per Box	5.98
Square Meters Per Box	5.00
Square Yards Per Pallet	191.36
Square Meters Per Pallet	159.98

Symbio TSYM

Carpet Tiles • Mainstreet Tiles - Nyluxe

Accessories



301 Carpet Tiles Adhesive - 4 U.S. Gallons

4 Gallons (15.14 Litres)

1/16" x 1/32" x 1/32" U-notch Trowel

Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

Non-Porous Coverage

680 - 760 sq.ft. / 4 Gallons (63 - 71 m² / 15 L)

- [🔗 Specifications - 301 Pressure Sensitive Carpet Tile Adhesive](#)
- [🔗 Label - 301 Pressure Sensitive Carpet Tile Adhesive](#)
- [🔗 SDS - 301 Pressure Sensitive Carpet Tile Adhesive](#)