



CHEMICAL RESISTANCE CHART

(ASTM F 925)

| CHEMICALS | Marathon | Electrotile / Texas Granite | TecCare / Mirra / Natura / Sonata / Sonata Elements / UltraCeramic Contract / Leaf |
|---|----------|-----------------------------------|--|
| White Vinegar (5%) | 0 | 0 | 0 |
| Rubbing Alcohol (70%) | 0 | 0 | 0 |
| White Mineral Spirits | 0 | 0 | 0 |
| Sodium Hydroxide NaOH (5%) | 1 | 0 | 0 |
| Hydrochloric Acid HCl (5%) | 0 | 0 | 0 |
| Sulphuric Acid H ₂ SO ₄ (5%) | 0 | 0 | 0 |
| Ammonium Hydroxide NH ₄ OH (5%) | 0 | 0 | 0 |
| Bleach NaOCl (5.25%) | 0 | 0 | 0 |
| Disinfectant Phenol (5%) | 0 | 0 | 0 |
| Olive Oil | 1 | 1 | 0 |
| Gasoline | 1 | 1 | 0 |
| Kerosene | 1 | 1 | 0 |

- Tests conducted on products direct from production, without surface treatment.
- One-hour test results.
- Coding system of results:
 - 0: no change;
 - 1: slight discoloration;
 - 2: moderate discoloration;
 - 3: severe discoloration.

Contact your American Biltrite representative for more data on chemical resistance.

Please note that technical web site documents prevail.

