



Collated Exterior Screws

PC Standing-Seam-Roofing Panel Clip Screw

Common Applications:

Standing-seam-roofing panel clips to wood

Features:

- Pancake head
- #2 square drive (driver bit in each box; replacement bit model BIT2SU)
- Type-17 point
- Straight collation

Codes/Standards: ASTM C1513 compliant

Warning: Industry studies show that hardened fasteners can experience performance problems in wet or corrosive environments. Accordingly, use this product in dry, interior and noncorrosive environments only.



Quik Guard® Coating

Length (in.)	Shank Size	Threads Per Inch	Carton Quantity	Model No.	PROPP150G2
1 1/2	#10	12	1,500	PCQ112BS1012	✓


WSC Wood Screw

Common Applications:

Wood to wood

Features:

- Flat head with nibs under the head for easier countersinking
- #2 square drive (replacement bit models BIT2SU)
- Coarse threads
- Curved collation



N2000® Coating

Length (in.)	Shank Size	Point Type	Carton Quantity	Model No.	PR0200SG2	PR0250G2	PR0300SG2
1 3/4	#8	Sharp point	2,000	WSCG134S	✓	✓	✓

Collated Interior Screws




WSC Wood Screw

Common Applications:

Wood to wood

Features:

- Flat head with nibs for easy countersinking
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- Coarse threads
- Available with Type-17 and sharp points
- Curved collation



Yellow Zinc Coating

Length (in.)	Shank Size	Point Type	Carton Quantity	Model No.	PRO200SG2
1 1/4	#8	Type-17	2,500	WSC114S-17	✓
1 1/2*	#8	Sharp	2,000	WSC112S	✓

* This size does not have nibs under the head.


WSCLT Wood Screw

Common Applications:

Wood to wood

Features:

- Flat head
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- Coarse threads
- Sharp point
- Yellow zinc coating
- Curved collation
- Fully threaded



Yellow Zinc Coating

Length (in.)	Shank Size	Carton Quantity	Model No.	PRO 200SG2	PRO 250G2
1 3/4	#8	2,000	WSCLT134S	✓	✓