



FLOOR MUFFLER® ULTRASEAL

floorMuffler® is a high performance **Acoustic Underlayment & Moisture Barrier**. Available both with and without UltraSeal self-sealing lip & tape system.

USES

Laminate, Engineered and Solid hardwood flooring installations.

METHODS

Floating, Nail down, and Double glue down installations.

APPLICATIONS



Residential



Commercial

MATERIAL


Cross Linked, Closed Cell Polypropylene Foam (XLPP)

THICKNESS

2 mm


PRODUCT SPECS

SPECS	STANDARD SIZE	CONTRACTOR SIZE
Coverage area	100 sf	600 sf
Width	39 in	72 in
Length	30.75 ft	100 ft
Diameter	6 in	9 in
Weight	2 lbs	12 lbs
Rolls/Carton	12	8
Carton/Skid	10	2




ACOUSTIC PERFORMANCE

74 IIC
73 STC
25 ΔIIC




MOISTURE PROTECTION

MVTR:
0.3 LBS
1000FT² - 24HRS.



THERMAL PERFORMANCE

R Value per inch:
4.3 FT²-F-HR/
BTU




COMPRESSIVE STRENGTH @25%

≥ 11 psi



FLAMMABILITY

CLASS A



ENVIROMENTAL

Mold & Mildew resistant:
YES

VOCs:
Compliant with CA 01350

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
1 800 440 6008

