

















































DESCRIPTION										
Family	SARLON NATURA	COLOUR	CONCRETE	CONTRAST	SLATE	STONE	STRIPE	TEXTILE	WOOD	WOVEN
Construction	Guaranteed "Phtalate Free". Heterogeneous commercial compact vinyl sheet flooring, reinforced with a glass fiber more recycled content backing						nesh and			
Туре	Authentic, realistic designs and colours creating a tailored flooring									
Standard	Commercial Use: Exceeds ASTM F1303 Type 1, Grade 1, Class B Backing									
Total Thickness	0.080" (2,0 mm)									
Wear Layer	0.028" (0,70 mm)									
Width	6'6" (2 m)									
Length	82 L.ft (25 mL)									
Roll Coverage	60 sq.y (50 m²)									
Weight	ht 5.3 lb/sq.y (2,9 kg/m²)									
Surface Finish	PUR PEARL: No	Wax, No S <sub>l</sub>	pray Buff, for th	e life of the pro	duct					

	PERFORMANCE	
	Chemical and Stain Resistance	Very good when tested in accordance with ASTM F925
Ð	Abrasion Resistance	ASTM F510: Best / EN 660-2: Group T
	Slip Resistance	Meets or exeeds the industry recommendations for flat surfaces when tested in acordance with ASTM D2047
	Static Load Resistance	Exeeds ASTM F970: 700 PSI
	Wheel Castor Resistance	Pass EN425: suitable for office chairs with castors
	Dimensional Stability	ISO 23999: < 0.1 %
3	Thermal Conductivity	EN12524: 0.25 W / mK Suitable for heated floors max 27°C (85°F)
	Impact Insulation Class	ASTM E989 (ASTM E492): IIC 40 / EN ISO 717-2: ΔL=7 dB
	Sound Transmission Class	ASTM E989 (ASTM E90): STC 53 / NF S 31-074: L < 75 dB class B
	Flame Spread and Smoke Development	Compliant with the Canadian Building Code when tested in accordance with CAN/ULC - S102.2
	ENVIRONMENTAL	

7	Micro-Organism Resistance	EN-ISO 846 Bacteriostat, no growth		
iii s	Indoor Air Quality, VOC Emission: v4, Credit 2	Compliant with CDPH 01350 Requirements		
	Low Emiting Material: Credit 4, option 1	Adhesive comply with SCAQMD Rule #1168		
	Recycled content 50% backing: Credit 4, option 2	100 % Recyclable		
)	Plants Certifications	ISO 9001, ISO14001, OHSAS 18001		
	Health and Safety	Complies with REACH regulation		
	Warranty: Limited 5 years	Special conditions & terms, on request		