

MSI

Making Dream Surfaces Attainable



Everlife

From MSI

HYBRID RIGID CORE
FLOORING

www.msisurfaces.com/Everlife

Colors




Avery Ash™



Brockton™



Delray™



Driftway™



Emridge™



Hillsdale™



Malton™

SMITHCLIFFS™ COLLECTION BY MSI

Total thickness		10 MM
Core tickness		8 MM
Attached Pad		2 MM
Wear Layer		20 MIL equivalent
Plank size		7.7" x 48"
Bevel		Painted/Beveled
ASTM F2199 (Dimensional Stability)		Passes
ASTM F1914 (Residual Indentation)		Passes (PSI Equivalent > 5,000 lbs.)
ASTM 648 (Radiant Panel)		>0.45 watts/CM2, NFPA Class 1
ASTM E662 (nbs smoke)		<450
ASTM (E492-09 / ASTM 989-06)		59 - drop ceiling / 47 - 6" sl
ASTM E90-09 (Sound Transmission Class)		STC 53
ASTM F925 (Resistance to Chemicals)		Passes
Scratch/Scuff/Abrasion Properties		Very Good
ISO 4918 Castor Chair		Passes @ 25,000 cycles
Installation System		Patented Locking System (Angle / Angle)
Certifications		FloorScore & Greenguard
Heavy Commercial Warranty		10-Year
HEAVY COMMERCIAL PASSING	Static Load	≥ 8MPa(1160psi)
	Thickness Swell	≤ 12%
	Light Resistance	No More than slight Effect
	Cleanability / Stain Resistance	Score < 20 No More Than Slight Effect
	Large Ball Impact Resistance	>1400 MM (55.1")
	Small Ball Impact Resistance	> 500 MM (19.7")
	Wear Resistance	≥ 6000 Cycles
	Dimensional Tolerance	Passes
	Chair Resistance	35,000 Cycles
	Surface Bond	1.5 N/MM²

Disclaimer:

MSI developed the most on-trend designs in luxury vinyl flooring with its Everlife® collection which includes high variation designs. It is recommended that the consumer go to www.msisurfaces.com/Everlife or view a display sample with room scene to see the high color variation. It also is recommended for a consumer to use a qualified installer who works with a recommended dealer, and will follow the installation instructions for Everlife® products.