Everlife®— FROM MSI

Waterproof Rigid Core Flooring

- GreenGuard Gold[®] Certified
- FloorScore® Certified
- · Installs on all grade-levels
- Pre-attached 1mm IXPE backing for quiet comfort.
- Coordinating trims available (Tmold, surface reducer, end cap, and stair nose)
- 100% Waterproof
- Uniclic® Locking System for easy installation

CYRUS SERIES:

Size: 7"x48" (nominal), 2.38 sqft/

piece

Thickness: 5mm

(4mm core + 1mm IXPE back) Wear layer: 12mil Warranty: lifetime limited residential, 10-year limited light

PRESCOTT SERIES:

Size: 7" x 48" (nominal), 2.38 sqft./

piece

commercial

Thickness: 6.5mm

(5.5mm core + 1mm IXPE back)

Wear layer: 20mil

Warranty: lifetime limited residential, 10-year limited light commercial, 5-year limited

commercial.



STABLE 7X48



SANDINO (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



WHITFIELD GRAY (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



RYDER (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



EXOTIKA (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



FAUNA (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



AKADIA (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



FINELY (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



KATELLA ASH (Cyrus Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



MEZCLA (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



LUDLOW (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



WEATHERED BRINA (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



HAWTHORNE (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



STABLE (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



BRALY (Cyrus, Prescott) 7"x48", 5MM thick, 12 MIL wear layer/7"x48", 6.5MM thick, 20 MIL wear layer



BARRELL (Cyrus) 7"x48", 5MM thick, 12 MIL wear layer



Everlife®— FROM MSI

Glue-Down Flexible LVT

- GreenGuard Gold Certified
- · FloorScore Certified
- · Installs on all grade-levels
- Coordinating trims available (Tmold, surface reducer, end cap, and stair nose)

KATAVIA SERIES:

Size: 6"x48", 2.00 sqft./piece

Thickness: 2mm Wear layer: 6mil Warranty: 15 year limited residential

GLENRIDGE SERIES:

Size: 6"x48", 2.00 sqft./piece

Thickness: 2mm

Wear Layer: 12mil Warranty: 25 year limited residential, 6-year limited light commercial

WILMONT SERIES:

Size: 6"x48", 7"x48" (Nominal) 2.47 sqft./piece

2.47 sqtt./piece
Thickness: 2.5mm
Wear Layer: 20mil
Optional sound mitigation
underlayment available
Warranty: lifetime limited
residential, 15-year limited
light commercial, 10-year
limited commercial



RECLAIMED OAK (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



ELMWOOD ASH (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



WOODRIFT GRAY (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



COASTAL MIX (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



CHARCOAL OAK (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



MIDNIGHT MAPLE (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



AGED HICKORY (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



JATOBA (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



BURNISHED ACACIA (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer 7"x48", 2.5MM thick, 20 MIL wear layer



TWILIGHT OAK (Katavia, Wilmont, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



BLEACHED ELM (Katavia, Glenridge) 6"x48", 2MM thick, 6 MIL wear layer/6"x48", 2MM thick, 12 MIL wear layer



LIME WASHED OAK (Wilmont, Glenridge) 6"x48", 2MM thick, 12 MIL wear layer/7"x48", 2.5MM thick, 20 MIL wear layer



SADDLE OAK (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer



TAWNY BIRCH (Glenridge) 6"x48", 2MM thick, 12 MIL wear layer