

# MSI

Making Dream Surfaces Attainable



Aspenwood  
Porcelain Collection

[www.msisurfaces.com](http://www.msisurfaces.com)



Colors



Amber 9"x48"



Artic 9"x48"



Ash 9"x48"



Café 9"x48"

Size	Thickness	AMBER	ARTIC	ASH	CAFÉ
9x48	3/8"	NASPAMB9X48	NASPART9X48	NASPASH9X48	NASPCAF9X48

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	DCOF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	IV	V3	SCOF - > 0.60 Wet DCOF > 0.42 Matte	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL		●	●						

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

Aspenwood is a large format wood plank with a contemporary look with high variations in print. The 9"x48" plank is non rectified with soft pillow edges to help the installation of this large tile to go smoothly. It's high definition ink jet and subtle texture gives it a very unique look when installed. Offered in four natural wood looking colors, this wider, longer wood tile will look excellent in every application.

Technical Information

Primary Colors: Amber, Artic, Ash, Café  
Material Type: Glazed Porcelain, Non-Rectified  
Finish: Matte finish with texture  
Polished: Hardness / Mohs 5  
Matte: Hardness / Mohs 7

Features At A Glance

- 9x48 non rectified ink jet wood plank
- Great looking graphic with contemporary looks
- Excellent price point for a large wood plank from Spain

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.

