

# MSI

Making Dream Surfaces Attainable



Balboa  
Ceramic Collection  
[www.msisurfaces.com](http://www.msisurfaces.com)

## Colors



Amber 6"x24"



Grey 6"x24"



Ice 6"x24"



Moka 6"x24"

Size	Thickness	AMBER	GREY	ICE	MOKA
6x24 Matte	5/8"	NBALAMB6X24	NBALGRE6X24	NBALICE6X24	NBALMOK6X24

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V3	DCOF - > 0.42	< 275 lbf	> 3%	5
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Non-Resistant	Resistant	Pressed	Glazed

Better than the real thing. Our red bodied Balboa Ceramic Tile Collection looks like wood but requires none of the upkeep and offers superior durability. In four statement-making colors: Amber, Grey, Ice, and Moka, this gorgeous 6"x24" wood-look collection works overtime to give your home interior a touch of natural luxury. On kitchen or living room floors, to countertops and accent walls, Balboa's classic style complements a wide variety of MSI products. Achieving that perfectly curated designer look has never been easier or more affordable.

### Technical Information

Primary Colors: Brown, Gray and White

Material Type: Ceramic

Finish: Matte

Polished: Hardness / Mohs 5

Matte: Hardness / Mohs 7

### Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

### Features At A Glance

- Unique Large Format 6X24
- 4 Colors In Wood Look
- 4 Colors Available In Matte Finish

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



### Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.