

MSI

Making Dream Surfaces Attainable



Bernini

Porcelain Collection

www.msisurfaces.com

Colors



Bianco 12"x24"



Camo 12"x24"



Carbone 12"x24"

Size	Thickness	BIANCO	CAMO	CARBONE
12x24 Polished	3/8"	NBERBIA1224P-N	NBERCAM1224P-N	NBERCAR1224P-N
12x24 Matte	3/8"	NBERBIA1224-N	NBERCAM1224-N	NBERCAR1224-N
2x4 Mosaic Polished	3/8"	NBERBIA2X4P-N	NBERCAM2X4P-N	NBERCAR2X4P-N
2x2 Mosaic Matte	3/8"	NBERBIA2X2-N	NBERCAM2X2-N	NBERCAR2X2-N
3x18 BN Polished	3/8"	NBERBIA3X18BNP-N	NBERCAM3X18BNP-N	NBERCAR3X18BNP-N
3x18 BN Matte	3/8"	NBERBIA3X18BN-R	NBERCAM3X18BN-R	NBERCAR3X18BN-R

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V3	Polished	> 275 lbf	< 0.5%	6
LIGHT COMMERCIAL	●	●	●			DCOF - < 0.42 Wet			
HEAVY COMMERCIAL		●	●			DCOF - > 0.42 Wet			

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

A luxurious linear look meets lovely neutrals and one-of-a-kind details in Bernini. Bernini Porcelain makes a style statement with its unique vein cut travertine look and fossilized veining in the most desired hues of whites, creams, and warm grays. Available in polished and matte finishes, this glazed tile collection offers several sizes, along with a coordinating decorative mosaic and bullnose to bring a touch of artistic style to your space.

Technical Information

Primary Colors: Beige, Grey, White
Material Type: Glazed Porcelain
Finish: Matte and Polished
Polished: Hardness / Mohs 5
Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer:

Wet Cutting Instruction: We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

Features At A Glance

- Luxurious porcelain (Matte and Polished) tiles with authentic marble looks and colorations
- Three great colors in a variety of sizes and trims
- High Definition Ink Jet Technology

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 18" Bullnose

