

MSI

Making Dream Surfaces Attainable



Essentials
Ceramic Collection

www.msisurfaces.com

Colors



Ansello Grey 12"x24"




Ansello Ivory 12"x24"



Charisma White 12"x24"



Charisma Silver 12"x24"



Vision Glacier 12"x24"



White Vena 12"x24"

Size	Thickness	ANSELLO GREY	ANSELLO IVORY	CHARISMA SILVER	CHARISMA WHITE	VISION GLACIER	WHITE VENA
12x24	3/8"	NANSGRE1224	NANSIVO1224	NCHASIL1224	NCHAWHI1224	NVISGLA1224	NWHIVEN1224
3x18	3/8"	NANSGRE3X18BN-R	NANSIVO3X18BN-R	NCHASIL3X18BN-R	NCHAWHI3X18BN-R	NVISGLA3X18BN-R	NWHIVEN3X18BN-R
2x2	3/8"	NANSGRE2X2	NANSIVO2X2				

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL	●	●	●	III	V3	DCOF - > 0.42 Wet	< 275 lbf	< 3.6%	6
LIGHT COMMERCIAL	●	●	●						
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Rectified	Glazed

The Essentials Collection consists of different exotic stone looks. All of these looks are offered in colors that fit today's trends. This attractive line in the popular 12"x24" format at near entry level price points is sure to excite your customers.

Technical Information

Primary Colors: Beige, Gray, Off-White, White
 Material Type: Glazed Ceramic
 Finish: Matte
 Polished: Hardness / Mohs 5
 Matte: Hardness / Mohs 7

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Disclaimer:

Wet Cutting Instruction We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

*No claims accepted after tile installation.

Features At A Glance

- Monocottura 12x24 size is one of the first in the market
- Rectified Ink jet at entry level price points
- Three exotic stone looks offering 6 different colors
- Coordinating 3x18 BN for all 6 colors

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.

Trim



3" x 18" Bullnose

