


# MSI

Making Dream Surfaces Attainable




Vintage  
Porcelain Collection

[www.msisurfaces.com](http://www.msisurfaces.com)



Colors



Lace 8"x36"

Silver 8"x36"

Size	Thickness	LACE	SILVER
8x36	3/8"	NVINLAC8X36	NVINSIL8X36

APPLICATIONS	Flooring	Counters	Wall	PEI Rating	Variation	COF	Breaking Strength	Water Absorption	Hardness
RESIDENTIAL				IV	V4	SCOF - > 0.60 Wet	> 275 lbf	< 0.5%	7
LIGHT COMMERCIAL									
HEAVY COMMERCIAL									

Freeze / Thaw	Chemical Resistance	Rectified/ Non-Rectified	Glazed / Non Glazed
Resistant	Resistant	Pressed	Glazed

The Vintage line has an old world barn wood look with a scraped painted finish affect. It is offered in four trendy contemporary hues including a white and a black. They are pressed with soft pillowed edges and come in a unique 8"x36" size.

Technical Information

Primary Colors: White, Brown, Gray, Silver  
Material Type: Glazed Porcelain  
Finish: Matte  
Polished: Hardness / Mohs 5  
Matte: Hardness / Mohs 7

Features At A Glance

- Unique 8x36 size
- Latest technology Italian Ink Jet design
- Trendy worn painted wood plank looks

Installation

1/8" Grout Size is recommended on all tile installation. When installing rectangular tiles a less than 33% staggered brick lay is strongly recommended.

Large format tiles: It is mandatory that the mortar coverage on the floor surface and tile be greater than 95% coverage to be fully supported. Voids due to insufficient coverage will result in cracking and tile displacement.



Disclaimer:

**Wet Cutting Instruction:** We recommend wet cutting or the score & snap method during the installation process. Do not dry cut product using power tools during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Recomendamos el corte en húmedo o el método de marcar y encajar durante el proceso de instalación. No corte en seco el producto utilizando herramientas eléctricas durante el proceso de instalación. Las técnicas de instalación inadecuadas podrían exponer al instalador a polvo de sílice nocivo.

Variation in shade is an inherent attribute of porcelain tile.

To ensure customer satisfaction: Make sure to look over all tiles before installing. Please select tile from same lot: same size, and numerical shade. Intersperse tiles throughout your job from different boxes. Rotate the tiles so there won't be repetitive patterns.

\*No claims accepted after tile installation.